



AC input voltage range	176~264VA	
AC input current	2A/230VAC	
Input frequency	47~63Hz	
Inrush current	40A/230VAC (cold start)	
Input leakage current	<0.5mA/230VAC	
Efficiency	>76%	
Output voltage	15VDC	-15VDC
Output current	0.2-3A	0-3A
Output voltage adjust range	±5%	not adjustable
Line regulation (full load)	≤±1%	≤±2%
Load regulation	≤±1%	≤±2%
Wave and noise	<150mVp-p	<200mVp-p
Output over current protection	110%-130%	regulator protection
Output over voltage protection	135%-150%	
Short circuit protection	Yes	Yes
Starting time	500ms	
Rise time	50ms@full load (typical)	
Hold up time	20ms@full load (typical)	
Operating temp	-10°C~+50°C	
Storage temp.	-25°C~+85°C	
Operating Humidity	20%~93%RH, non condensing	
Storage temp	20%~95%RH, non condensing	
MTBF	100000hours	
Cooling method	convection	
Mechanical structure	with enclosure	
Size	199×98×39mm	
Connection	TB9.5 terminal block	
Warranty term	2 years	
Withstand voltage	I/P-O/P: 1.5KVAC/1min	
	I/P-F/G: 1.5KVAC/1min	
	O/P-F/G: 0.5KVAC/1min	
Safety standard	GB4943, UL60950, EN60950	
EMC standard	GB9254, EN55022, EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11	