



## HI-REV HYDRAULIC OIL 32, 46, 68 ANTIWEAR HYDRAULIC FLUID

### Product Description

HI-REV HYDRAULIC OIL is quality hydraulic oil containing antiwear and foam inhibitor for use in both high and low pressures hydraulic system.

### Performance Standards

HI-REV HYDRAULIC OIL meets the general industrial specifications for industrial and mobile hydraulic systems, which calls for:

- ❖ Denison HF-2
- ❖ Vickers I-286-S, M-2950-S
- ❖ Cincinnati Milacron P-68, P-69, P-70
- ❖ Commercial Hydraulic\*

\* Except for PM-500 series silver containing pumps.

### Customer Benefits

- Proven field performance.
- Excellent thermal and oxidative stability.
- Good hydrolytic stability.
- Excellent demulsibility ensuring rapid water separation from oil.
- Good rust protection.
- Low filter blockage tendency.
- Excellent antifoam characteristic.
- Offers high protection against wear
- Compatible with most hydraulic seal materials.

### Typical Applications

HI-REV HYDRAULIC OIL is designed for all types of hydraulic systems meeting general specifications.

### Typical Properties

Characteristic	ASTM Method	HI-REV HYDARULIC OIL		
		32	46	68
ISO VG		32	46	68
Viscosity, cSt@40 Deg C	D 445	31	44	65
	@ 100 Deg C	D 445	5.35	6.58
Viscosity Index	D 2270	105	100	99
Flash point Deg C (Typical)	D 92	210	220	230
Pour point Deg C	D 97	-15	-15	-15