



HT GREASE 777 (WHITE)

Spanjaard HT GREASE 777 (WHITE) is a white NLGI No. 2 consistency lubricant, for use as a long term grease in key applications and also as an assembly and anti-seize compound where cleanliness is of prime importance.

APPLICATIONS

For grease lubrication of food and bottling machinery, photocopiers, typewriters, and printing machines; vacuum cleaners, washing machines, dishwashers, tumble dryers; adjustable awnings, garage door slides; precision instruments; optical equipment; textile and packaging machinery; fridges and deep freezers; splines and sliding surfaces; anti-seize for all types of bolts, nuts and fasteners.

APPLICATION INSTRUCTIONS

Apply a coating by brush or chamois. Anti-friction bearings are either prepacked or relubricated by a grease gun.

ADVANTAGES

Long service life grease with high load carrying capacity due to solid lubricant content. Functions as a highly fortified grease in high load; high temperature conditions. Prevents stick slip; Resists fretting corrosion. Good water resistance. Low co-efficient of friction in threaded connections. Effective to 1200°C in anti-seize applications.

Colour	White
Thickener	Lithium
Operating Temp °C	-20 to 120
Drop Point, °C	250
Mineral oil content, %	85
Oil V.I.	95
Oil viscosity at 100°C, cSt	18
Worked penetration, 25°C, 1/10mm	280
Solid submicron lubricant	white dispersion
EP additive	Additional



HANDLING AND STORAGE

Minimise skin contact. Store under cover away from vibrating floor. See also safety data sheet.

PACKAGING

500g Tin; 5kg Tin; 15kg Keg

TYPICAL PROPERTIES

CP/mg/HT Grease 777 (White) – May 2016