


CASSIDA FLUID WG Series

Product Information

Synthetic high performance gear lubricants for worm gear boxes used in the food and beverage processing equipment



CASSIDA FLUID WG 220, 320, 460, 680 and 1000 are high performance, anti-wear gear oils for the lubrication of worm gears, highly loaded gears and applications where high resistance to micro-pitting is needed, for the use in food and beverage processing equipment.

They are based on a careful blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- Kosher
- Halal
- DIN 51517 CLP
- ISO 6743/6 L-CKD, CKE



PERFORMANCE FEATURES

- High resistance to micro-pitting
- Neutral odour and taste
- Provide excellent thermal stability, load carrying properties and corrosion protection. Resistant to the formation of harmful oxidation products
- Exceptional low friction providing efficient power transmission. Measured worm gear efficiency is high relative to other oils
- Water solubility ideal for use in situations where equipment gets routinely cleaned before and after use and where some water might penetrate into the lubricant
- Does NOT mix with mineral oils or PAO

CHANGE OVER PROCEDURES

When changing from a lubricant based on mineral oil or PAO, the following procedure **must** be followed: The equipment should be at normal operating temperature, then the oil drained off as fully as possible. Special attention should be paid to reservoirs, lines etc. where oil may be trapped. Then the system **must be flushed with the new lubricant**, which should then be drained before refilling with fresh, new lubricant. **Note:** Seals previously exposed to mineral oils may shrink when exposed to CASSIDA FLUID WG. This can result in oil leaks. It may therefore sometimes be necessary to replace them.

SEAL AND PAINT COMPATIBILITY

Compatible with most of the elastomers, gaskets and seals normally used in food machinery lubrication systems. Nitrile rubber (NBR), Fluoro-Silicone or Vinyl-Methyl Polysiloxane (Q) are recommended especially where high temperatures are involved. Polyurethane based elastomers, leather, cork, asbestos paper and board should be avoided.

Note: see warning about seal shrinkage in section on change-over procedures. Some ordinary industrial paints soften in the presence of CASSIDA FLUID WG. Internal gearbox surfaces should ideally be unpainted or coated with resistant material such as two-part epoxy formulations.

HANDLING AND STORAGE


All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

			CASSIDA FLUID WG				
			220	320	460	680	1000
Property		Test Method					
NSF Reg. No.			144785	144786	144787	144788	145430
Colour			Clear, amber				
Density at +15 °C	kg/m ³	ISO 12185	1057	1062	1067	1072	1079
Flashpoint	°C	ISO 2592	249	251	254	258	270
Pourpoint	°C	ISO 3016	-42	-39	-36	-33	-30
Kin. Visc. at +40 °C	mm ² /s	ISO 3104	227	339	477	725	1005
Kin. Visc. at +100 °C	mm ² /s	ISO 3104	41.9	60.6	83	122	163
Viscosity index		ISO 2909	240	250	260	272	280
FZG-Test A/8.3/90 Failure Load Stage		ISO 14635-1	> 12				

APPLICATIONS

- Especially recommended for use in worm gears and applications where excellent thermal stability is required
- Lubrication of enclosed gear boxes used in the food industry
- High load carrying capability, for extreme pressure applications



FUCHS LUBRITECH GMBH
Werner-Heisenberg-Straße 1
67661 Kaiserslautern / Germany
T: +49 (0) 6301 3206-0 / F: +49 (0) 6301 3206-940
www.fuchs-lubritech.com

 A Member of the
FUCHS PETROLUB Group

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: cassida.lubricants@fuchs-lubritech.de