



COMET SYSTEM, s.r.o.

Bezrucova 2901

756 61 Roznov pod Radhostem

CZECH REPUBLIC

Tel.: +420 571 653 990

E-mail: info@cometsystem.com

H6520 - remote CO₂ concentration thermometer hygrometer with Ethernet interface and two relays



code: H6520

Temperature, humidity, CO₂ level sensor with two output relays. Humidex reading.

Sensor H6520 is designed for online monitoring of temperature, relative humidity of air without aggressive substances. Other devices are controlled by two relay outputs. High precision capacitive polymer sensor ensures excellent long term calibration stability and ultimate accuracy. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy.



The CO₂ measurement is based on a 2-source, 2-beam process. CO₂ measurement with long-term stability is guaranteed thanks to the proven non-dispersive infrared (NDIR) CO₂ measurement cell. The unique patented auto-calibration procedure compensates for aging of the infrared source and guarantees high reliability, long term stability and eliminates the need of periodical recalibration in the field.

Included in delivery:

- H6520 sensor
- [Traceable calibration certificate](#)
- Quick start manual
- Technical support at [discussion forum](#)

Transmitter is also equipped with three alarm LEDs:

Green LED shines - CO₂ concentration 0 to 1000 ppm

Yellow LED shines - CO₂ concentration 1001 to 1200 ppm

Red LED shines - CO₂ concentration 1201 ppm and more

Features

APPLICATIONS:

• Building management

The CO₂ - carbon dioxide level is recently regarded as an important parameter that substantially determines the quality of the interior climate. Especially in buildings where many people gather, such as meeting rooms, hospitals, schools, cinemas, theatres and care centres. With the help of CO₂ sensor engineers, technical advisors, environmental experts and health specialists can optimize the ventilation for creation of a healthy interior climate.

CO₂ monitoring of buildings, history data to [Comet Database](#), remote alarm by email or SMS

• Warehouses

CO₂ monitoring of storage, history data to [Comet Database](#) or 3rd party SCADA system

• Factories and manufacturing

CO₂ monitoring for food processing industry, pharmaceutical industry, etc.



SOFTWARE:

• Comet Database

Complex solution for data acquisition and analysing. Easy to use and high flexible database software for Comet Sensors.

• T-Sensor software

Free configuration utility for COMET sensor.

• SensorReader software

Basic data acquisition utility for COMET Sensors. Software is free for download.

• 3rd party software

[Cacti](#), [InTouch](#), [ControlWeb](#), [EasyView](#), [LabVIEW](#). Support for this software is provided by the 3rd party companies.

FEATURES:

CO₂ concentration



Method of CO₂ sensor multipoint calibration leads to an excellent accuracy measurements of CO₂ in the entire of operating temperature range. With this sensor is the device able to meet the demanding requirements for outdoor use. The measurement principle is based on the NDIR principle with dual wavelength, which automatically compensates for aging of the sensor. The sensor is resistant against the pollution and provides maintenance-free operation and excellent long-term stability.

Temperature and humidity



Sensor is designed to measuring from internal temperature and humidity sensor. High precision capacitive polymer sensor ensures excellent calibration long term stability, inertia against water and condensation. Web Sensor is designed for use in non-aggressive environment. Degrees Celsius and Fahrenheit are user selectable.



Humidex



The humidex (humidity index) is an index number used by meteorologists to describe how hot the weather feels to the average person, by combining the effect of heat and humidity. The term Humidex is a Canadian innovation. The reading is in °C.

Dew point and computed quantities



Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy. User can select one of these interpretation.

Relay outputs



Two relay output for alarming or external device control. It is possible to assign any input value to each relay. Relay can be remotely controlled using ModbusTCP communication protocol.

Dual line LCD



Large dual line LCD for simultaneous display of temperature, relative humidity, CO₂ concentration or other calculated humidity interpretation is an advantage. Displayed values are user selectable. Display can be switched off.

Acoustic alarms



Acoustic signalisation can be activated after exceeding set limits. Alarm can be confirmed (deactivated) from device keyboard.

Ethernet interface



10Base-T/100Base-TX Ethernet interface via standard RJ45 connector. IP address can be obtain automatically from DHCP server or set manually. Internet protocol version 4 is supported only.

WWW server



Current values are available via embedded web server. Design of the web pages is can be changed according user requirements.

Email



Warning email are sent when measured value exceed selected limits. SMTP authentication is supported, but SSL not.

History export to CSV



History values can be exported for next processing by the CSV file. CSV file can be processed inside spreadsheet application like Microsoft Excel or OpenOffice Calc. Two formats of CSV file are supported - dot and comma decimal point separators. Timestamps inside CSV file are shown when device time is synchronised by the SNTP server.

ModbusTCP protocol



Modbus protocol for communication with SCADA systems or third party software. Device use Modbus TCP protocol version.

SNMP protocol



SNMP version 1 protocol for IT infrastructure. Using SNMP protocol you can read actual measured values, alarm status and alarm parameters. Via SNMP protocol is also possible to get last 1000 measured values from history table. MIB tables with OID description are available..

SNMP Trap



SNMP Trap for IT infrastructure. The device allows sending Traps to selected Trap receiver server. Traps are sent in case of alarm on channel or at error states.

SOAP protocol



The device allows to send currently measured values via SOAP v1.1 protocol. The device sends values in XML format to the web server. The advantage of this protocol is that communication is initialized by the device side. Due to it is not necessary use port forwarding.

Syslog protocol



Syslog protocol for IT infrastructure monitoring systems. The device allows sending text message to selected Syslog server. Messages are sent in case of alarm on channel or at error states.

SNTP protocol - time synchronization



Time synchronisation with SNTP server. Actual time is shown at web pages and is necessary for timestamps inside CSV files.

Technical Data

Technical parameters	Value
Output	Ethernet
Measured Value	CO ₂ + Temperature + Relative Humidity
Construction Type	Ambient Air
Design	Industrial
Temperature Measuring Range	-30 to 60 °C
Relay Output	Yes
Two-State Input	No
Lcd Display	Yes
PoE	No

Range of CO ₂ concentration measurement	0 to 2000ppm
Accuracy of CO ₂ concentration measurement	±(50ppm +2% from reading) at 25°C and 1013hPa
Optional range of CO ₂ concentration measurement	0 to 10000ppm ±(100ppm +5% from reading) at 25°C and 1013hPa
Relative humidity range	0 to 100%
Accuracy of relative humidity measurement	±2.5% relative humidity from 5 to 95% at 23°C
Accuracy of temperature output	±0.4°C
Resolution	0.1°C, 0.1%RH, 1ppm
Measuring interval of temperature and relative humidity	2s
Measuring interval of CO ₂	15s
Available temperature units	degrees Celsius, degrees Fahrenheit
Computed values	humidex, dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Accuracy and range of dew point temperature output - for more details see graphs in manual	±1.5°C at ambient temperature T<25°C and RH>30% range -60 to +80°C
Accuracy and range of absolute humidity output	±1.5g/m ³ at ambient temperature T < 25°C range 0 to 400g/m ³
Accuracy and range of specific humidity output	±2g/kg at ambient temperature T < 35°C range 0 to 550g/kg
Accuracy and range of mixing ratio output	±2g/kg at ambient temperature T < 35°C range 0 to 995g/kg
Accuracy and range of specific enthalpy output	±3kj/kg at ambient temperature T < 25°C range: 0 to 995kj/kg
Temperature compensation of the humidity sensor	all temperature range
Temperature operating range	-30 to +60°C
IP protection	IP30
Number of relay outputs	2
Maximum switching voltage, current and power of relay output	50V, 2A, 60VA
Audible alarm	built-in beeper - switchable
LAN connection	RJ-45 connector, 10Base-T or 100Base-TX
Communication protocols	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail (SMTP authentication is supported), SNMP Trap, Syslog
Configuration	WWW interface, T-Sensor
Power	9 to 30Vdc, power consumption approximately 1W
Power connector	co-axial, diameter 5.5 x 2.1mm
Dimensions	136 x 213 x 45mm (W x H x D), stem length 75mm
Weight	approximately 340g
Warranty	3 years