

DC PULSE TIG/MMA

# VT-215P

TIG Welding Power Source

## Quick Specs

### Light Industrial Applications

Maintenance Repair  
Shipboard Installation  
Fabrication  
Hobbyist  
Process Piping

### Power Voltage

1 Phase AC240V ±15%  
50/60Hz

### Input Current

25A/6kVA

### Output Current

2-200A  
Max. OCV: 42VDC

### Output Voltage

18V

### Duty Cycle

60%

### Weight

9KG

### Dimensions

D375×H232×W155MM

## Portable. Professional. Rugged. Affordable.

The inverter **VT-215P** offers much more than you would expect from a welder this size. Weighing in at just under 9kg the Inverter **VT-215P** is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

### FEATURES

- DC inverter for TIG with advanced inverter technology to optimize arc performance.
- Improved TIG Starting. Now starts DC(-) to maintain a sharp tungsten.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- 200 amps @ 60% duty cycle is the highest output rating in this machine class.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.
- **Built-in pulsing functions**  
LF: 0.5~1.5Hz  
MF: 5~15Hz

### PROCESSES

DC TIG (GTAW)  
MMA



### INCLUDED

VT-215P Machine Only Includes:

- VT-215P
- 7M WP26F-1 TIG TORCH.
- 3M work cable and clamp.

### INPUT



### OUTPUT



### AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3  
TAMAN BATU GAJAH PERDANA  
31550 PUSING PERAK MALAYSIA  
TEL: (605)3632 115 FAX: (605)3632 111  
E-mail: [austcorp@welding.com.my](mailto:austcorp@welding.com.my)  
WEB: [www.welding.com.my](http://www.welding.com.my)



Welding Technology