

GS SERIES	GS6500			GS5500		
Model Number	030590	030576	030598	030574	030575	030572
Watts* (Rated)	6,000	6,000	6,000	5,000	5,000	5,000
Watts* (Maximum)	6,500	6,500	6,500	5,500	5,500	5,500
Volts (VAC)	115/230	230	230	230	230	230
ENGINE						
CC	420	420	420	420	420	420
Gross Horsepower*	13.5	13.5	13.5	13.5	13.5	13.5
Starting System	Rewind Start	Rewind Start	Rewind Start	Rewind Start	Rewind Start	Rewind Start
Oiled Foam Air Cleaner	•	•	•	•	•	•
Low Oil Shutdown	•	•	•	•	•	•
Dura-Bore™ Cast Iron Sleeve	•	•	•	•	•	•
Dual Ball Bearings	•	•	•	•	•	•
AC SOCKETS						
120V/15A US	2	-	-	-	-	-
230V/16A Schuko	-	2	-	2	-	1
230V/13A UK	-	-	-	-	2	-
230V/30A Twist Lock	1	1	2	1	1	1
230V/32A LeGrand Schuko	-	-	-	-	-	1
GENERATOR FEATURES						
Phase	Single	Single	Single	Single	Single	Single
Frequency	60Hz	60Hz	60Hz	50Hz	50Hz	50Hz
Dimensions (mm, l x w x h)	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564
Dry Weight (kg)	81	81	81	81	81	81
Noise Level (at 7m)	78.8 dB(a)	78.8 dB(a)	78.8 dB(a)	75.3 dB(a)	75.3 dB(a)	75.3 dB(a)

GS SERIES	GS6500E			GS5500E		
Model Number	030591	030583	030599	030579	030580	030578
Watts* (Rated)	6,000	6,000	6,000	5,000	5,000	5,000
Watts* (Maximum)	6,500	6,500	6,500	5,500	5,500	5,500
Volts (VAC)	115/230	230	230	230	230	230
ENGINE						
CC	420	420	420	420	420	420
Gross Horsepower*	13.5	13.5	13.5	13.5	13.5	13.5
Starting System	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start
Oiled Foam Air Cleaner	•	•	•	•	•	•
Low Oil Shutdown	•	•	•	•	•	•
Dura-Bore™ Cast Iron Sleeve	•	•	•	•	•	•
Dual Ball Bearings	•	•	•	•	•	•
AC SOCKETS						
120V/15A US	2	-	-	-	-	-
230V/16A Schuko	-	2	-	2	-	1
230V/13A UK	-	-	-	-	2	-
230V/30A Twist Lock	1	1	2	1	1	1
230V/32A LeGrand Schuko	-	-	-	-	-	1
GENERATOR FEATURES						
Phase	Single	Single	Single	Single	Single	Single
Frequency	60Hz	60Hz	60Hz	50Hz	50Hz	50Hz
Dimensions (mm, l x w x h)	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564	724 x 527 x 564
Dry Weight (kg)	81	81	81	81	81	81
Noise Level (at 7m)	78.8 dB(a)	78.8 dB(a)	78.8 dB(a)	75.3 dB(a)	75.3 dB(a)	75.3 dB(a)

* Generators are rated in accordance with CSA (Canadian Standards Association) standard C22.2 No. 100-04 (motors and generators) and rated in accordance with PGMA (Portable Generator Manufacturers' Association) standard PGMA 200 (Standard for Testing and Validating Performance of Portable Generators). † All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

Briggs & Stratton reserves the right to change specifications, features or pricing without notice. Product may vary from images shown.



UK



Twist Lock



US