

BS-2513
BS-2016
BS-2516
BS-3016
BS-2030

激光裁床

Laser Cutting Bed



铝条平台
Aluminum platform

坚固耐用的铝条平台，合适压克力、木版等材料的加工。

Solid and durable aluminum platform, suitable for acrylic, board and other materials processing.



工业冷却机(压缩机制冷)
Industrial cooling machine



USB加密狗
USB SOFTWARE DOG

功能与并口加密狗一样，采用USB接口设计，使用更加方便。适合笔记本等，没并口的电脑设备使用。

Function and parallel SOFTWARE DOG is the same. Adopt USB interface design, use more conveniently and suitable for notebook and no parallel port use of the computer equipment.

激光管采用强制水冷却方式，温度自动控制，缺水报警，确保激光管能连续工作。

The laser tube adopts compulsive water cooling system ,it can control the tem perature automatically,it will alarm if there is a shortage of water thus ensure the continuous work of the laser tube.

特点描述/Description

开放式的工作平台方便了加工材料的放置，并可配合流水线的工作。

The open working platform is suitable for processing materials and working trend.

满足了大幅面加工和大数量加工

The machine can meet the requirement of large-scale processing.

设备采用混合式光路，光能利用率高，光路全封闭式，安全性强

The machine have hybrid-type path of ray, high-usage of light energy , totally-enclosed type and high safety characters.

加工面料范围广，切口平滑无飞边，自动收口，无变形，图形可通过电脑随意设计等特点。

The machine can processing different materials, which cutting smooth and non-shrinkage in the materials. You can design any pictures as you need.

质量优良，价格合理

Excellent in quality and reasonable in price.

应用行业/Applicable Industries

服装打样、大幅面截断、皮革业、鞋业、装饰业、家具业、广告业、包装印刷业、模型业、工艺礼品业等。

Garments sampling, large width tailoring, leather industry, shoemaking, decoration, furniture, advertisement, packing and printing, molding and art craftindustries, etc.

适合材料/Applicable Materials

布料、皮革、纸张、竹木制品、有机玻璃、玻璃、薄膜、帆布等。

Fabrics, leather, paper, bambooware, Lucite, glass, films and canvas, etc.

相关参数/Parameters of Products

产品型号 TYPE	BS-2513	BS-2016	BS-2516	BS-3016	BS-2030
雕刻面积 Engraving area	1300×2500mm	1600×2000mm	1600×2500mm	1600×3000mm	2000×3000mm
雕刻速度 Engraving speed		0-64000mm/min (无级调速/stepless speed regulating)			
激光功率 Laser power			80w / 120w / 150w		
分辨率 Resolution ratio			0.025mm		
最小成形文字 Minimum shaping character		汉字/Chinese Character	2mm 字母/letter 1mm		
重复定位精度 Resetting positioning accuracy			±0.01mm		
电源 Power supply		AC220V±10%,50HZ			
总功率 Gross power	<2500w	<2500w	<2500w	<2500w	<3000w
工作温度 Operating temperature			0°C-45°C		
工作湿度 Operating humidity		5%-95% (无凝水/free of condensed water)			
支持图文格式 Graphic format supported		BMP、GIF、JPEG、PCX、TGA、TIFF、PLT、CDR、DWG、DXF			
整机重量 Net weight	450KG	480KG	500KG	550KG	650KG
外形尺寸 Dimension	2400×1800×1100mm	2800×1800×1100mm	2600×2100×1100mm	3600×2100×1100mm	3600×2500×1100mm
可选配件 Optional		工业冷却机、蜂窝平台 (Cooling Machine、Honeycomb Platform)			

以下资料如有变动恕不另行通知
All content are subject to change without notice