

HARD, TOUGH AND LIGHTWEIGHT SEMI TRAILER, SR-50F-B



HARDNESS	
HARDOX 450	MILD STEEL
450 HB	132 HB

YIELD STRENGTH	
HARDOX 450	MILD STEEL
1,250 MPa	275 MPa

MATERIALS

- Base Plate : 6 mm Hardox-450
- Side Wall : 5 mm Hardox-450
- Front Wall : 5 mm Hardox-450
- Rear Door : 5 mm Hardox-450
- Top Beam : 5 mm Hardox-450

DIMENSIONS*

- Length : 10,760 mm
- Height : 1,524 mm
- Width : 2,500 mm
- Volume : 38.34 m³

*To be varied according to inspection plan

WHAT'S IMPORTANT TO US IS WHAT COUNTS FOR YOU

- Wear Resistance Hardox-450 Wear Plate
- Reduced Deformation (Eliminate Worn Spot)
- High Impact Resistance
- Reduced Tare Weight
- Increased Service Life
- Greater Volume
- Increased Payload
- Higher Load Capacity
- Improved Fuel Efficiency
- Reliable Edbro Front End Tipping Cylinder
- Lower CG Design (Lower Risk to Roll Over)
- 45° Curved Floor Avoid Load Sticking on the Corner
- Flat Internal Face make Lower Tipping Angle and Faster Discharge Rate
- Flat Faces for Side Wall Allowed to put Decals to Promote Company Business
- 2K Painting for Rust Protection and Superior Finishes



BUATAN MALAYSIA
MADE IN MALAYSIA

