

Description

405PT-WPB is a 2 gang Decora style HDBaseT wall-mountable transmitter for HDMI or VGA/audio and RS232 at 230ft (70m) transmission with PoC function. It supports Auto-switching or button panel control between the inputs

Features

- * Integrated with HDBase T Technology
- * 230 ft (70m) transmission with PoC function
- * HDMI or VGA with audio input selectable.
- * Built in scaling function, output resolution up to 4K
- * Auto switching or button manual control between input sources.
- * LEDs for status checking & USB for firmware update
- * Aluminium design for elegant & nice cooling



Technical Specifications

Input	1 HDMI (HDMI female), 1 VGA (VGA female), 1 AUDIO (3.5mm mini jack), 1 RS232 (3P captive screw connector)
Output / Transmission Mode	1 HDBaseT (RJ45) / HDBaseT
Resolution	Up to 1080P for VGA; 800 X 600 ~ 1920 x 1200, 3D & 4K x 2K for HDMI
Gain	0dB~10dB @ 100MHz
Transmission Distance	230ft (70m)(max)
Differential Phasic Erro	$\pm 10^\circ$ @ 135MHz~100M
Bandwidth / Return Lost	10.2Gbps / <-30dB @ 5KHz
HDMI Standard / Min-Max Level	Support HDMI1.4 & HDCP / 0.3V~1.45Vp-p; 75Ω
Power Supply	12V DC; 9.6W
Temperature / Chassis Dimension	-20%~+90% / Decora style two gang

