



HB1080IR(MV)

2MP Motorised Varifocal IR Bullet Camera



Key Features

- * 2 Megapixel high-performance CMOS
- * Analog HD output, up to 1080P resolution
- * 2.8 - 12mm motorized vari-focal lens
- * True Day/Night, Smart IR
- * Up to 40m IR distance
- * IP66 weatherproof & vandal proof
- * OSD menu
- * 24 VAC / 12VDC(-A)
- * Up to Coax

Specification

DETAILS		HB1080IR(MV)
Camera	Image Sensor	2MP CMOS Image Sensor
	Signal System	PAL/NTSC
	Effective Pixels	1930(H)*1088(V)
	Min. illumination	0.01 Lux@(F1.2,AGC ON),0 Lux with IR; 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
	Shutter Time	1/25(1/30)s to 1/50,000s
	Lens	Motorized VF lens; 2.8 - 12 mm @ F1.4
		Angle of view: 114.5° - 35.1°
	Lens Mount	φ14
	Day & Night	ICR
	Angle Adjustment	Pan: 0° - 360°; Tilt:0° - 90°; Rotate: 0° - 360°
	Synchronization	Internal synchronization
	Video Frame Rate	1080p@25fps/1080p@30fps
	HD Video Output	1 Analog HD output
	S/N Ratio	> 62dB
Menu	Camera ID	On/off (0-255)
	AGC / BLC	Support
	D/N Mode	Color/BW/Auto/EXT
	White Balance	Auto/User/Push/8000K/6000K/4200K/3000K
	Privacy Mask	On/Off, maximum 2 zones
	Motion Detection	On/Off, maximum 4 zones
	Anti-flicker	On/Off
	Language	English/Chinese
	Functions	Digital noise reduction, Mirror
	General	Operating Conditions
Power Supply		12 VDC±15%; -A: 12 VDC±15% 24 VAC±15%,
Power Consumption		Max. 5W; -A: Max. 6W
Protection Level		IP66
IR Range		Up to 40m
Communication		Up the coax
Dimension		92 × 84.8 × 269.6mm(3.62" × 3.34" × 10.6")
Weight		900 g