



## D1080IR(MV)

Motorised Vari-focal Dome Camera

### Key Features

- \* Adopt 1/2.8" SONY CMOS Sensor
- \* Auto Gain Control (AGC)
- \* Auto Electronic Shutter (AES)
- \* Gama Characteristic
- \* Scanning Mode
- \* IP66

### Specification

| DETAILS               | D1080IR(MV)  |
|-----------------------|--|
| Image Sensor          | 1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor |
| Resolution            | 1080P  |
| Signal System         | PAL / NTSC   |
| Min illumination      | 0.001 lux/ F1.2  |
| S/N Ratio             | More than 52dB   |
| Synchronous System    | Internal   |
| IR Distance           | 30 Meters (with 14μx24pcs Infrared LED)                |
| IR Power On           | Photodiode AUTO Control                                |
| Video Output          | CVBS / CVI / TVI / AHD                                 |
| Power / Current       | DC12V(+/-10%) 700mA                                    |
| Lens                  | 2.8~12mm Motor Zoom & Auto Focus Lens                  |
| Weather Proof         | IP66   |
| WDR                   | Yes  |
| UTC                   | Yes  |
| OSD                   | Yes  |
| Dimension (mm)        | 125(W) x 105.8(H) x 135(D)                             |
| Weight (g)            | 800  |
| Storage Temperature   | -30°~ +60°C, RH95% MAX                                 |
| Operating Temperature | -10°~ +50°C, RH95% MAX                                 |