



# Kodio

## KHA-130HV20T KHA-200HV20T

Vandalproof IR Dome Camera

### Key Features

- \* Adopt CMOS 1/3" Sensor
- \* Auto Gain Control (AGC)
- \* Auto Electronic Shutter (AES)
- \* Gama Characteristic
- \* Scanning Mode

### Specification

DETAILS	KHA-130HV20T	KHA-200HV20T
Pick up Element	1/3" SONY 1.4 Megapixel CMOS Sensor	1/2.7" OV CMOS Sensor
Effective Picture Elements (HxV)	1305(H) x 1049(V)	1920(H) x 1080(V)
Horizontal Resolution	720P	1080P
Min illumination	0.001 lux/ F1.2	
Electronic Shutter	1/25s~1/50,000s, 1/30s~1/60,000s	
S/N Ratio	More than 50dB	
Scanning System	Progressive	
Synchronous System	Internal, Negative sync.	
IR Distance	20 Meters (with $\phi$ 5x24 Unit Infrared LED)	
IR Status	Under 10 Lux by PD	Under 10 Lux CDS
IR Power On	PD Auto Control	CDS Auto Control
Video Output	TVI	
Auto Gain Control	Auto	
NR	2D/3DNR (Auto)	
White Balance	Auto	
Power / Current	DC12V(+/-10%) 550mA	
Lens	Board Lens 3.6mm / F2.0	
Dimension (mm)	$\phi$ 89 x 76(H)	
Weight (g)	450	
Storage Temperature	-30°~ +60°C, RH 95% MAX	
Operating Temperature	-10°~ +50°C, RH 95% MAX	