



BI080IR(V/622)

Weatherproof VF Box Camera

Key Features

- * Adopt CMOS 1/2.8" Sensor
- * Auto Gain Control (AGC)
- * Auto Electronic Shutter (AES)
- * Weatherproof Aluminum Housing
- * Scanning Mode
- * Water resistance : IP66

Specification		
Camera	Image Sensor	1 / 2.8" Sony 2.4MP COS
	DSP	FH8531
	Image Resolution	25fps@1080P(1920×1080)
	Effective Pixels	1920(H)×1080(V), 2MP
	TV System	PAL/NTSC
	Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
	Sync System	Internal
	Usable Illumination	0.01Lux
	S/N Ratio	≥50dB
	Scanning System	Progressive Scan
	Video Output Mode	TVI(BNC)
Lens	Focus Length	6-22mm
	Focus Control	Manual
	Lens Type	Manual
	Pixels	2M Pixels
Night Vision	Infrared LED	¢42X4PCS
	Infrared Distance	80M
	IR Status	Under 10 Lux by CDS
	IR Power On	CDS Auto Control
Camera Features	Noise Reduction	DNR
	OSD Support	No
General	Weatherproof Housing	IP66
	Anti-cut Bracket	YES, 3-Axis
	IR Cut Filter	YES
	Operation Temperature	-10°C ~ +50°C RH95% Max
	Storage Temperature	-20°C ∼ +60°C RH95% Max
	Power Source	DC12V±10%, 1000mA
	Dimension	230(W)x180(H)x115(D)mm
	Weight	2.5Kg

