



# Kodio

## DVIP-20IR(MV)

2MP IP Dome Camera With Zoom Lens

### Key Features

- \* 2.8-12mm Focal Length
- \* Motorised lens, auto focus
- \* Auto Gain Control (AGC)
- \* ONVIF
- \* WDR
- \* IP66

### Specification

DETAILS	DVIP-20IR(MV)
Image Sensor	IMX322
Main processor	S2L
Resolution / Effective Pixels	1080P/720P / 1920(H)*1080(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Focus Length / Pixels	2.8-12mm Auto Zoom / 3M Pixels
Focus Control/ Lens Type	Auto Zoom
Infrared LED/ Infrared Distance	14μ x 24PCS/ ϕ 5 (12μ) /30M
IR Status / IR Power On	Under 10 Lux By CDS / CDS Auto Control
Ethernet / ONVIF	RJ-45 (10/100Base-T) / Support ONVIF 2.4
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
P2P / POE	YES, Support QR Code / Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream / Sub Stream	1920*1080@25fps@30fps / 720*576@25fps@30fps
IE Brower	IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)
Smart Phone	iPhone, iPad, Android, Android Pad
Day/Night	Color/ B&W (IR-CUT )
Compression	H.264/JPEG,Support record AVI format.
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection / Privacy Masking/WDR	Support / 3 Rectangular Zone/ YES
Wide Dynamic Range	WDR
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Housing	IP66
Anti-cut Bracket	YES, Anti-Cut Bracket
IR Cut Filter	YES
Operation Temperature / Storage Temperature	-10°C ~ +50°C RH95% Max / -20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension / Weight	125(W)x105.8(H)x135(D)mm /800g