



Kodio

DVIP-13IR DVIP-20IR

IR Dome Network Camera

Key Features

- * Dual stream
- * IR Range : 20M
- * Board Lens 3.6mm/F2.0
- * IR LED ϕ 5X24PCS

Specification

DETAILS	DVIP-13IR	DVIP-20IR
Image Sensor	1/3"Sony CMOS 1.3MP	1/2.9"Sony CMOS 2.4MP
Main Processor	HI3518C	HI3516C
Resolution	720P/960P	1080P
Effective Pixels	1280(H)*720/960(V)	1920(H)*1080(V)
TV System	PAL / NTSC	
Electronic Shutter Time, Sync Systems	Auto: PAL 1/1-1/10000 Sec; NTSC1/1-1/10000 sec, External	
Usable Illumination / SN Ratio	0.01 Lux / \leq 52dB	
Scanning System / Video Output	Progressive / Network	
Focal Length / Focus Control	3.6mm/ Fixed	
Lens type	2MP HD Lens	3MP HD Lens
Infrared LED / Infrared Distance	ϕ 5x24pcs / 20M	
IR Status / IR Power On	Under 10 Lux By CDS / CDS Auto Control	
Ethernet	RJ-45 (10/100 Base-T)	
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS	
ONVIF	Support ONVIF 2.4	
P2P / PoE	Yes, Support QR Code / Optional, Support IEEE 802.3af	
WiFi, Video Delay	N/A , 0.3S (within the LAN)	
Main Stream	1280*720/960	1920*1080
Sub Stream	720*576, 352*288	
Smart Phone	iPhone, iPad, Android, Android Pad	
Day / Night	Color / B&W (IR-Cut)	
Compression	H.264/JPEG, Support record AVI Format	
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, BLC, FLK (Flicker Control)	
Motion Detection/ Privacy Masking/WDR	Support / 3 Rectangular Zone/ No	
Recording Mode	NVR/NAS/CMS/Web	
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian	
Housing / Adjustment / IR Cut Filter	Vandalproof (metal) / No, Without Bracket / Yes	
Operating Temperature/ Storage Temperature	-10 $^{\circ}$ ~+50 $^{\circ}$ C, RH 95% MAX / -20 $^{\circ}$ ~+60 $^{\circ}$ C, RH 95% MAX	
Dimension (mm)	ϕ 89 x 76(H)	
Weight (g)	450	