



## HD DVR-7304/7308/7316

HD1080P Realtime Recording DVR

## **Key Features**

- Connectable to HD-TVI and analog cameras
- Connectable to the Coaxitron camera/dome with long transmission distance.
- Simultaneous HDMI, VGA and CVBS outputs; HDMI output and VGA output at up to 1920 x 1080P resolution.
- New GUI and support starting record with one key.
- Redundant recording and holiday recording schedule configuration.
- Instant playback for assigned camera during multi-channel live view mode.
- Support up to 16ch synchronous playback at 1080P resolution, and reverse playback for multichannel.
- Smart playback to go through less effective information.
- Manual video quality diagnostics.
- Customization of tags, searching and playing back by tags.
- Locking and unlocking record files.
- Support HDD quota and group management; different capacity can be assigned to different cameras under quota mode.
- Provide 4 SATA interfaces and 1 eSATA interface for record and backup.
- 1 self-adaptive 10M/100M/1000M network interfaces.
- Support Kodio DDNS (Dynamic Domain Name System);
- Network detection function.

## Introduction

DVR-7300 series DVR (Digital Video Recorder) is a new generation recorder developed by Kodio independently which can connect HD analog cameras and provide powerful surveillance. Combined with multiple advanced technologies, such as audio and video encoding & decoding technology, embedded system technology, storage technology, network technology and intelligent technology. It can both work alone as a recorder and corporate with other devices to build a comprehensive surveillance system.

The DVR-7300 series DVR are widely applied in the areas of finance, public security, military, communication, transportation, education, etc.

## **Physical Interfaces**

3 7 13 2	15 14	10
00000000000000000000000000000000000000		
1 4 5	6 8 9	12 11

Index	Name	Index	Name
1	VIDEO IN	9	RS-485 Serial Interface, Keyboard Interface, ALARM IN and ALARM OUT
2	VIDEO OUT	10	100 ~ 240 AV Power Input
3	AUDIO IN, RCA Connector	11	Power Switch
4	USB Port	12	GND
5	HDMI Interface	13	LINE IN
6	VGA Interface	14	eSATA Interface
7	CVBS AUDIO OUT and VGA AUDIO OUT	15	RS-232 Serial Port
8	LAN Network Interface		

Specification (KODIO HD DVR-7300 Series DVR)								
Item		HD DVR-7304	HD DVR-7308	HD DVR-7316				
	Video compression		H.264					
	Analog and HD-TVI	4-CH	8CH	16CH				
	video input	BNC interface (1.0Vp-p, 75Ω)						
Video/ Audio Input	Support camera types	720P25, 720P30, 720P50, 720P60,1080P25, 1080P30, CVBS						
	Audio compression	G.711u						
	Audio input / Two-way audio in	4-ch, RCA (2.0Vp-p, 1kΩ) / 1-ch, RCA (2.0 Vp-p, 1 kΩ)						
	HDMI / VGA output	1920 x 1080 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz						
	CVBS output	1-ch, BNC (1.0 Vp-p, 75Ω), resolution: PAL:704 x 756, NTSC: 704 x 480						
	E P	Main stream : 1080P/ 720P / VGA/ 4CIF / CIF						
	Encoding resolution	Sub-stream: WDI (non-real-time) / 4 CIF (non-real-time) / CIF / QCIF / QVGA						
	Formeral	Main stream : 1/16fps ~ Real time frame rate						
Video / Audio	Frame rate	Sub-str	ne rate					
output	Video bitrate	32Kbps- 10 Mbps						
	Audio output	2-ch, RCA (Linear, $1k\Omega$ , VGA output and CVBS output respectively)						
	Audio birate	64 Kbps						
	Dual-stream	Support						
	Stream type	Video, Video & Audio						
	Synchronous playback	4-ch	8-ch	16-ch				
	Playback resolution	1080P / 720P / VGA / WDI / 4CIF / CIF / QVGA / QCIF						
Natural management	Remote connection	128						
Network management	Network protocols	TCP/IP,PPP₀E,DHCP,DNS,DDNS,NTP,SADP,SMTP,SNMP,NFS,iSCSI,UPnP™,HTTPS						
I lead dist	Туре	4 SATA interface for 4 HDDs; 1 eSATA interface						
Hard disk	Capacity	Up to 4 TB capacity for each disk						
	Network interface	1;10M / 100M / 1000M self-adaptive Ethernet interfaces						
External interface	Serial interface	RS-232, RS-485, Keyboard						
External interface	USB port	3 x USB2.0						
	Alarm in / out	16 / 4						
	Power supply	100 ~ 240 VAC, 47 ~ 63Hz						
	Consumption (without hard disk)	<u>&lt;</u> 30W	<u>&lt;</u> 40W	<u>&lt;</u> 55W				
	Working temperature	-10°C~+55°C (14°F~131°F)						
General	Working humidity	10% ~ 90%						
	Chassis	19-inch rack-mounted 1.5U chassis						
	Dimensions (WXDXH)	445 x 390 x 70mm						
	Weight (without hard disk)	≤ 5KG						