

Features

- Slim edge design with low side profile
- Rated Input : 6W
- Speaker Driver Unit : 2" / 5" / 6"
- Spring clip installation
- Option for installation without enclosure
- High quality ABS enclosure with optional FR grade



Description

Introducing a newly designed ceiling speakers, KCS-602, 605 and 606 which break away from the normal outlooks and are now portrayed as cosy with its slim edge baffle.

Three variants are available with re-engineered sound output to serve the needs for both BGM and EVAC. KCS602 is a miniature version most suitable for small enclosed area such as hotel room foyer and narrow corridors, while KCS-605 and KCS-606 fits most other installations according to the needs of different coverage areas.

Technical Specifications

	KCS-602	KCS-605	KCS-606
Power rating	6W 100V line		
Diameter	2" (51 mm)	5" (125 mm)	6" (150 mm)
Cone Type	Single cone	Dual Cone	
Impedance (Ohm)	8		
Freq response @ 1KHz +/-3 dB	160 - 15 KHz	150 - 19 KHz	120 - 19 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz)	90 dB	92 dB	
Tapping (100V line)	1.5 / 3 / 6W		
Primary impedance (Ohm)	6.7K / 3.3K / 1.67K		
Secondary Impedance (Ohm)	8		
Grille / Enclosure	Metal / ABS enclosure		
Cutting hole dim	85 mm	145 mm	185 mm
Overall Size (Dia x Height)	110 x 110 mm	165 x 110 mm	205 x 110 mm
Weight	500 g	740 g	840 g
Colour	White		