



Description

The KCS-50SA is a powered subwoofer that can be mounted on the wall, the floor or next to the wall in a way that hides the control panel. The product reproduces low-range audio frequencies and includes auto standby and adjustable crossover frequencies.

Features

- Powered subwoofer
- With rubber surround
- Continuous program
- RCA connector, 2 high-level inputs
- 220-240VAC

Technical Specifications

Active Powered Subwoofer	KCS-50SA
Frequency response	30Hz ~ 600kHz@-10dBB, 45Hz to 350Hz @+/-3dB
Woofer	8" (203mm) aluminum with rubber surround
Impedance / Sensitivity	200Ω / 95dB SPL, 1W@1m
Max SPL	Continuous: 108dB; peak: 114dB
Built In Power amplifier	50W RMS, 140W continuous program
Power source	Selectable: 110-120VAC 60Hz or 220-240VAC 50Hz
Crossover frequency	65-150Hz
Input connector	High-level unbalanced stereo audio on binding posts, LFE on line level unbalanced stereo audio on RCA connectors
Controls	Volume, crossover, phase, auto standby and selectable power source
Materials	Wooden cabinet and wooden bracket
Operating temperature	-15° to 70°C
Storage Temperature	-30° to 55°C
Humidity	25% to 90%, RHL non-condensing
Included Accessories	Power cable, 4 black rubber feet
Dimension (cm) / Weight	45(W) x 40(D) x 20.50(H) / 10.3kg