

### Features

- Versatile Ceiling Speaker
- Designed for a Variety of Indoor Applications
- Rated Input : 6W
- Speaker Driver Unit : 4"
- Impedance : COM/10k $\Omega$ /3.3k $\Omega$ /1.6k $\Omega$
- Frequency Response : 100Hz – 18kHz
- Durable White Finish



### Description

The KCS-06S is a versatile surface mount speaker that is designed for a variety of indoor applications. The speaker employs a full range speaker unit and incorporates a matching transformer for efficient operation. Power handling is rated at 6W/100V. The speaker features a steel mesh speaker cover in a durable white finish. The speaker's casing is made of ABS resin.

### Technical Specifications

<b>Power (Rated) / Tapping (W)</b>	<b>6W (Rated) / 1, 3 &amp; 6W</b>
<b>Impedance</b>	<b>10/3.3/1.6k<math>\Omega</math></b>
<b>Magnet</b>	<b>Ferrite</b>
<b>Speaker Dimensions/Type</b>	<b>4" / full range</b>
<b>Frequency Response</b>	<b>100Hz – 18kHz</b>
<b>SPL (1w/1m)</b>	<b>90 dB</b>
<b>Dimension(WXHXD)</b>	<b>195 X 215 X 105</b>
<b>Net Weight</b>	<b>0.75 kg</b>