

Features

- 6 mic / line selectable input channels, with front mic jack, phantom power
- Priority muting for mic input 1 with adjustable muting level
- 3 zone speaker output with ALL CALL and remote triggering port
- 100V line output with aux 4 Ohm speaker terminal
- Tone and bass controls
- AC / DC operation
- USB / SD Card / Tuner / Bluetooth Player



Technical Specifications

Rating	240W 100V line
Operating Voltage	220 - 240V AC or 24V DC
24V DC requirement	15A
Current (Load / Standby)	4.1A / 15A
Input channel	6 : 2 MIC (XLR), 4 MIC/Line Selectable (RCA/Phone Jack)
Input phantom power	Mic 1 and 2 ; 12V DC
Input Sensitivity / impedance	2 x Mic (XLR) & 4 x Mic (Phone jack) : 20 mVrms 4 x LINE (RCA) : 150 mVrms
Tone controls	Bass (100 Hz) ; Treble (10 KHz) +/- 3 dB
Outputs	3 Zone 100V line, 4 Ohm
Output selection	Front and remote triggering
Frequency response @ 1KHz +/- 3dB	70 ~ 15 KHz
Protections	Thermal, short circuit, AC and DC fuse
Indicators	AC mains, clip, protect, audio input level
Cooling system	Dual speed fan with heat sensing
Dimensions (WxHxD)	424 x 88 x 300 mm
Weight	12.8 kg