

## SURFACE MOUNT CEILING SPEAKER

**KCS-605S** 

## **Features**

- •High Quality ABS Material for Long Lasting Usage
- Multitap Transformer in 1.5/3/6W 100V
- Unique Honeycomb ABS Grille for Pleasant
  Outlook and rust Free

 $\bullet \ Impedance: 8k\Omega$ 

• Frequency Response : 150Hz - 17kHz



## **Description**

The KCS-05 is a general purpose ceiling surface mount speaker, suitable for slab mounting. Its dual cone driver delivers good sound reproduction for speech and background music.

## **Technical Specifications**

Barrar Batina	CW 400V line memired (men 400W)
Power Rating	6W 100V line nominal (max 100W)
Diameter	5" (125 mm)
Cone Type	Dual Cone
Impedance (Ohm)	8
Freq Response (+/- 5dB)	150 ~ 17 kHz
SPL@1W/m (+/- 3dB) 1 KHz	92dB
Magnet Weight	3 oz
Tapping (100V Line)	1.5/3/6W
Primary Impedance (Ohm)	6.7K/3.67K/1.7K
Secondary Impedance (Ohm)	8
Grille / Enclosure	ABS Plastic
Overall Size (dia x height)	222 x 65 mm
Net Weight	700g
Colour	White and Black

