

### Features

- ❑ Commercial public address system ceiling speaker with transformer.
- ❑ Hi-fi range coaxial ceiling loudspeaker with back cover.
- ❑ Ideal for school, restaurant, hotel, train station & airport BGM and speech use.
- ❑ High power output range in-ceiling speaker for big scale pa system installation.
- ❑ Rated power output 2.5W-5W-10W-20W at 100V.
- ❑ Rated power output of 20W RMS.
- ❑ 5" coaxial PP two way driver unit with breathing hole.
- ❑ Line input 100V or 70V & 8Ω.
- ❑ ABS enclosure, metal grille and metal back can in white.
- ❑ Flush mount in-ceiling quick and secure installation.
- ❑ Wide dispersion rang installation PA loudspeaker.



### Technical Specifications

<b>Model</b>	<b>KCS-20M</b>
<b>Description</b>	<b>5" Coaxial Ceiling Speaker</b>
<b>Rated Power Output</b>	<b>2.5W-5W-10W-20W</b>
<b>Line Input</b>	<b>100V or 70V &amp; 8Ω</b>
<b>Frequency Response</b>	<b>100-20KHz</b>
<b>SPL(@1W/m)</b>	<b>88 dB</b>
<b>Speaker Unit</b>	<b>5" coaxial PP two way driver unit</b>
<b>Cutout Size</b>	<b>170mm</b>
<b>Dimension</b>	<b>203(D)×145(H)mm</b>
<b>Cutout Size</b>	<b>Ø205mm</b>
<b>Dimensions</b>	<b>Ø235×145mm</b>
<b>Material</b>	<b>ABS enclosure, metal grille and metal back can in white</b>
<b>Mounting Way</b>	<b>Flush mount in-ceiling quick and secure installation</b>
<b>Weight</b>	<b>1.7kg</b>