



Rear Panel

Features

- ❑ All weather loudspeakers for music applications and projects.
- ❑ Ideal for indoor outdoor BGM and paging system.
- ❑ IP66 waterproof finish for all extreme weather applications
- ❑ 6.5" weatherproof woofer and 1" silk tweeter 2-way speaker system.
- ❑ ABS enclosure, stainless metal grille & stainless mounting bracket
- ❑ Power output 40-20-10-5-2.5W & 8Ω
- ❑ 70V/100V speaker with power tapping or as a low impedance 8 Ohm speaker
- ❑ Waterproof cable wiring cover for IP66 secure weatherproof protection
- ❑ Ultra- reliable, fail safe loudspeaker even at high power loads
- ❑ Supplied with 360° rotatable bracket for horizontal and vertical installation angle adjustment

Technical Specifications

Model	KBS-40
Description	Indoor Outdoor Wall Mount Speaker
Rated Power Output	40W and Max. 80W
Power Tap	40-20-10-5-2.5W & 8Ω
Line Input	100V or 70V & 8Ω
Frequency Response	65-20KHz
SPL(@1W/m)	94±3dB and Max 112dB (1m)
IP Rate	IP66
Speaker Unit	6.5" weatherproof woofer and 1" silk tweeter 2-way speaker system
Dispersion	Vertical: 180° and Horizontal: 180° (1KHz)
Dimensions	280×150×180mm
Material	ABS enclosure, stainless metal grille & stainless mounting bracket
Color	White
Mounting Way	360° rotatable bracket for horizontal and vertical installation angle adjustment
Weight	3.5kg