

**ACESys**



**DK-282 I (P)**

#### FEATURES & SPECIFICATIONS

- 1,000 User PINs and/or EM Cards
- 50 Visitor Codes with Programmable Valid Time for Guests and Temporary Staff
- User Controlled Lockup on After Office Hours or Nobody at Home
- Programmable System Lockup for False Trials
- Auto or Manual Code Entry
- Intelligent Egress Button with Programmable Conditions for "Going Out"
- ON-OFF Programmable for The Pacifier Tone & The Flashing LED
- N.C. & N.O. Relay Dry Contacts Compatible with Fail-safe and Fail-secure Electric Locks
- 50mA/24VDC Max Tamper Switch N.C. Dry Contact
- Operating Voltage: 12 VDC Nominal, 11-15VDC
- Operating Current: 50mA(Quiescent), 120mA Max.
- -20 Deg C to +70 Deg C
- 5-95% Relative Humidity, Non-Condensing
- ABS plastic Housing

**DK-2821(P) -- FLUSH/SURFACE MOUNT KEYPAD**

RED  
 AMBER  
 GREEN

FIXING SCREWS X 2

**CONNECTION TERMINALS**

1	2	3	4	5	6	7	8
TAMPER	(+)	(-)		OUTPUT 1			EG
N.C.	12V DC			N.C.	COM	N.O.	IN

**ADDITIONAL PRODUCT FEATURES**

- Epoxy Coated Silicone Rubber Back-lit Keyboard
- Stainless Steel Faceplate
- 5A/24VDC Max. N.C. & N.O. Output Relay Dry Contacts
- Indoor Use Only, IP-50
- Weight : 180gs
- Size : 117(H) x 72(W) x 43(D)mm
- Fits Standard U.S Single Gang Box
- Flush Mount on Gang Box or Surface Mount on The Supplied Plastic Box
- Popular Version of The DK-2821