

PM-K5100 ALL IN ONE TERMINAL



- #Key!Features!**
- #Flat!Touch!Screen!**
- #Water!Splash!Resistant!**
- #Easy!Maintenance!Tool!**
- #Big!Screen!2nd!Display!**

Product Specifications

Model	PM-K5100-D1	PM-K5100-D2	PM-K5500-D15
Mainboard	Intel Celeron Bay Trail D J1900 Quad Core up to 2.4G (2M Cache Fanless)		Intel® Core™ i5-3317U Processor 3M Cache, up to 2.60 GHz
CPU			
Memory	4GB DDR-III 1333 (Option to 8GB)		
Hard Disk	64GB mSATA SSD (Option to 128GB SSD)		
Monitor Size Brightness Contrast	15" FLAT LED SCREEN (1024*768) 450cd/m2 700:1		
Touch Screen	5 wire Resistive touch screen – Flat Screen	Projective Capacitive touch screen – Flat Screen	5 wire Resistive touch screen – Flat Screen
IO port	COM*2 USB*6 LAN*1 DC12V*1 Audio*1		
Display	20*2 VFD – K5000		
Second Screen	15" Flat Screen (PM-K5100-M15)	15" Flat Screen (PM-K5100-M25)	15" Flat Screen (PM-K5500-M15)
MSR	External USB MSR		
Power Supply	External 12V-5A Adapter		
Working temperature	0°C-40°C (32°F-104°F)		
Storage temperature	-10°C-50°C (14°F-122°F)		
Operating Humidity	10%-80%		
Carton Size	500(L)x300(W)x470(H)		

CCI POS Solutions (002627730-A)

A-G-10, Jalan Bangau 11, Bandar Puchong Jaya, 47100 Puchong, Selangor, Malaysia.

Tel: +603-80705880 Fax: +603-80705882

info@cci.com.my