INDOOR/OUTDOOR LOCKABLE WALL BOX UP TO 12 FIBERS



The FIBER-REX FR-WB35 Lockable IP65 distribution box is supplied unloaded and offers the ability to terminate 12 fibers in a strong and robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat solution for housing 12 SC simplex connections and splices. The box has 12 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A locking feature adds extra security when positioned in an un-secure area.

Features

- IP 65 Rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 12 splice & SC connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 12 exiting cables + 2 incoming cable
- Removable door for ease of installation
- Supplied with 12 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps
- RoHS, REACH & SvHC compliant

Applications

- Data centers, premise installations, telecommunication networks
- Ethernet, Fiber Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Indoor/outdoor applications

Technical Specification

Parameters	Value
Height	235mm
Width	205mm
Depth	60mm
Net weight	0.9kg
IP rating	IP65
Suitable for adapter type	SC Simplex
Number of ports	12
Cable entry	2
Material	ABS
Color	Grey RAL 7035
Operating temperature	-40°C to +60°C
Compliant to	Compliant to RoHS, REACH/SvHC

Ordering Information

Part No.	Description
FR-WB35XXX00	Indoor/Outdoor IP65 Rated Lockable Wall box up to 12 Fibers