

# INDOOR/OUTDOOR LOCKABLE WALL BOX UP TO 48 FIBERS



Closed view

Open view

This standard FIBER-REX FR-WB32 Lockable IP65 distribution box is supplied unloaded and offers the ability to terminate 48 fibers in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable adapter tray provides a neat solution for housing 48 SC simplex connections and splices. Integrated cable tie points are included to secure incoming cables. A locking feature adds extra security when positioned in un-secure areas.

## ★ Features

- IP 65 Rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 12 splice & SC connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 12 exiting cables + 2 incoming cable
- Removable door for ease of installation
- Supplied with 12 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps
- RoHS, REACH & SvHC compliant

## ✓ Applications

- Data centers, premise installations, telecommunication networks
- Ethernet, Fiber Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Indoor/outdoor applications

## ⚙️ Technical Specification

Parameters	Value
Height	420mm
Width	320mm
Depth	125mm
IP rating	P65
Adapter Type	SC Simplex or LC Duplex
Number of Adapter Positions	48
Splice Tray Type	8 Cores
Max. Splicing Capacity	96 Splices
Material	PC+ABS
Color	White
Operating temperature	-40oC to +60oC
Compliant to	RoHS, REACH/SvHC

## 🛒 Ordering Information

Part No.	Description
FR-WB32XXX00	Indoor/Outdoor IP65 Rated Lockable Wall box up to 48 Fiber