



Smart phone's App based on iOS and Android system :

- iOS® version installed in Apple mobile phone, which required iphone 5s model or above.
- Android[™] version installed in Android[™] mobile phone,
 which required version 6.0 or above.

The smart phone's App needs to assign a card number (authorization) before it works with BT Reader.









www.entrvpass.net

EP.BSR / EP.BSKR Bluetooth Multi-technologies Reader

Modes of Access:

- Show-to-Go: Show the mobile phone in front of the reader to open the door (same as swipe a card)
- Shake-to-Go: Shake the mobile phone to open the door (NOT to turn the mobile phone).
- Hands free: door opened automatically when mobile phone entered in connecting area.
- Manual Button: click the button in the APP to open the door manually.

Security

Since Bluetooth does not carry any security element, all the communication and data stored inside the App are encrypted with AES128. The authentications as follows:

- 1st Authentication: Dynamic key is used to authenticate both Bluetooth reader and App.
- 2nd Authentication: Reader will check if the App assigned repeated Customer Code.
- 3rd Authentication: Reader will check if the App assigned repeated End User Code.

Bluetooth Reader & Mobile Phone Apps

- Bluetooth reader supports both Bluetooth + Mifare And /Or DesFire + 125KHz technologies.
- Bluetooth reader can set different reading distance from 0.1m to 5m.
- Support IN/OUT reader configuration.
- Enter password in case of change configuration in the App, allow authorized user to configure: reading range of reader, name a reader, set different Modes of access and modes of IN/OUT reader.
- The App supports Manual Active Button when the app is running normally.
- When there is more than one reader within the reading range, all the names of readers will be popped up on the screen for user to choose which reader should be activated.
- The App shows the strength of detected Bluetooth signal.
- The App supports to run in the background mode of mobile phone.
- Supports to set a validation period of authorization.



EP.85R / EP.85KR

Bluetooth Multi-technologies Reader

Reconfiguration Window 5 seconds (Default) or Half an hour after Power up Reading Technologies Bluetooth & Mifare & DesFire&125KHz BT Antenna Directional Keypad Output N/A 4bits(default)/8bits/26bits Buzzer Control Reader & Controller control (Default) Read Range BT is configurable 1m~5m; Wiring Distance 150m (22 AWG with shielded cable) Apps Specifications Operating System Both iOS & Android Data Encryption Customer Code + End User Code + AES128 Show-to-Go Reading distance is adjustable Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C-70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White Operating Humidity 10% -90%	Reader Specifications			
Bluetooth & Mifare & DesFire&125KHz BT Antenna Directional Keypad Output N/A 4bits(default)/8bits/26bits Buzzer Control Reader & Controller control (Default) Read Range BT is configurable 1m-5m: Wiring Distance 150m (22 AWG with shielded cable) Apps Specifications Operating System Both iOS & Android Data Encryption Customer Code + End User Code + AES128 Show-to-Go Reading distance is adjustable Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Specification: Operating Current 150mA (max) Operating Temperature -30°C-70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material Standard Color Black or White		Standard Reader	: Keypad Reader	
BT Antenna Directional Keypad Output N/A : 4bits(default)/8bits/26bits Buzzer Control Reader & Controller control (Default) Read Range BT is configurable 1m-5m; Wiring Distance 150m (22 AWG with shielded cable) Apps Specifications Operating System Both IOS & Android Data Encryption Customer Code + End User Code + AES128 Show-to-Go Reading distance is adjustable Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Reconfiguration Window	5 seconds (Default) or Half	5 seconds (Default) or Half an hour after Power up	
Keypad OutputN/A4bits(default)/8bits/26bitsBuzzer ControlReader & Controller control (Default)Read RangeBT is configurable 1m~5m;Wiring Distance150m (22 AWG with shielded cable)Apps SpecificationsOperating SystemBoth iOS & AndroidData EncryptionCustomer Code + End User Code + AES128Show-to-GoReading distance is adjustableShake-to-GoPhone vibrate when motion is successShake SensitivityAdjustableOperating Specification:Operating VoltageOperating Current150mA (max)Operating Temperature-30°C -70°CExterior dimension115.5mm x 84.5 x 20.5mmCase materialPC+ABSStandard ColorBlack or White	Reading Technologies	: Bluetooth & Mifare & DesFire	: Bluetooth & Mifare & DesFire&125KHz	
Buzzer Control Reader & Controller control (Default) Read Range BT is configurable 1m~5m; Wiring Distance 150m (22 AWG with shielded cable) Apps Specifications Operating System Both iOS & Android Data Encryption Customer Code + End User Code + AES128 Show-to-Go Reading distance is adjustable Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	BT Antenna	: Directional	: Directional	
Read Range BT is configurable 1m~5m; Wiring Distance 150m (22 AWG with shielded cable) Apps Specifications Operating System Both iOS & Android Data Encryption Customer Code + End User Code + AES128 Show-to-Go Reading distance is adjustable Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C-70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Keypad Output	: N/A	: 4bits(default)/8bits/26bits	
Wiring Distance 150m (22 AWG with shielded cable) Apps Specifications Operating System Both iOS & Android Data Encryption Customer Code + End User Code + AE\$128 Show-to-Go Reading distance is adjustable Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Buzzer Control	Reader & Controller control	Reader & Controller control (Default)	
Apps SpecificationsBoth iOS & AndroidData EncryptionCustomer Code + End User Code + AES128Show-to-GoReading distance is adjustableShake-to-GoPhone vibrate when motion is successShake SensitivityAdjustableOperating Specification:10 - 15VDCOperating Current150mA (max)Operating Temperature-30°C -70°CExterior dimension115.5mm x 84.5 x 20.5mmCase materialPC+ABSStandard ColorBlack or White	Read Range	BT is configurable 1m~5m;	BT is configurable 1m~5m;	
Operating SystemBoth iOS & AndroidData EncryptionCustomer Code + End User Code + AES128Show-to-GoReading distance is adjustableShake-to-GoPhone vibrate when motion is successShake SensitivityAdjustableOperating Specification:Operating VoltageOperating Voltage10 - 15VDCOperating Current150mA (max)Operating Temperature-30°C -70°CExterior dimension115.5mm x 84.5 x 20.5mmCase materialPC+ABSStandard ColorBlack or White	Wiring Distance	: 150m (22 AWG with shielded	150m (22 AWG with shielded cable)	
Data EncryptionCustomer Code + End User Code + AE\$128Show-to-GoReading distance is adjustableShake-to-GoPhone vibrate when motion is successShake SensitivityAdjustableOperating Specification:Operating Voltage10 - 15VDCOperating Current150mA (max)Operating Temperature-30°C -70°CExterior dimension115.5mm x 84.5 x 20.5mmCase materialPC+ABSStandard ColorBlack or White	Apps Specifications			
Show-to-Go Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Operating System	Both iOS & Android	Both iOS & Android	
Shake-to-Go Phone vibrate when motion is success Shake Sensitivity Adjustable Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Data Encryption	Customer Code + End User	Customer Code + End User Code + AES128	
Shake Sensitivity Operating Specification: Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Show-to-Go	Reading distance is adjusta	Reading distance is adjustable	
Operating Specification: 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Shake-to-Go	: Phone vibrate when motion	Phone vibrate when motion is success	
Operating Voltage 10 - 15VDC Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Shake Sensitivity	: Adjustable	: Adjustable	
Operating Current 150mA (max) Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Operating Specification:	:		
Operating Temperature -30°C -70°C Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Operating Voltage	: 10 - 15VDC	: 10 - 15VDC	
Exterior dimension 115.5mm x 84.5 x 20.5mm Case material PC+ABS Standard Color Black or White	Operating Current	: 150mA (max)	: 150mA (max)	
Case material PC+ABS Standard Color Black or White	Operating Temperature	: -30°C -70°C	: -30°C-70°C	
Standard Color Black or White	Exterior dimension	: 115.5mm x 84.5 x 20.5mm	: 115.5mm x 84.5 x 20.5mm	
	Case material	PC+ABS	PC+ABS	
Operating Humidity 10% - 90%	Standard Color	Black or White	Black or White	
	Operating Humidity	10% - 90%	10% - 90%	
Weight : 210g	Weight	: 210g		

Ordering information:

EP.BSR700 - Bluetooth enabled reader that support multi card format (125KHz & 13.56MHz) with OSDP protocol
EP.BSKR700 - Bluetooth enabled keypad reader that support multi card format (125KHz & 13.56MHz) with OSDP protocol
EP.BSR700-Wie - Bluetooth enabled reader that support multi card format (125KHz & 13.56MHz) with wiegand protocol
EP.BSKR700-Wie - Bluetooth enabled keypad reader that support multi card format (125KHz & 13.56MHz) with wiegand protocol



www.entrypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong, Batu 12 Jalan Puchong, 47160 Puchong Selangor Darul Ehsan, Malaysia. Tel :+603 8068 1929

Fax : +603 8062 6937 Email : info@entrypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building, Singapore 408555.

Tel : +65- 6841 7242 Fax : +65- 6841 3937 Email : info@entrypass.net

Indonesia

Rukan Puri Mutiara, Block BF No.17, Jln Griya Utama, Sunter Agung, Jakarta Utara, 14350, Indonesia.

Tel : +62 21 2937 6098 Email : indonesia@entrypass.net