

1-MS SEALANT

MODIFIED SILICONE

LOW MODULUS

- Non-Staining
- Low VOC
- Excellent Durability
- Excellent Sealing



Rovski Industries Sdn. Bhd.

Lot 561, Jalan Subang 3, Subang Jaya Industrial Park, 47610 Subang Jaya, Selangor Darul Ehsan, Malaysia.
Tel: 03-56332908 Fax: 03-56341186 Website: <http://www.rovski.com.my> | Online Store: <http://www.allfix.com.my>

1-MS SEALANT

Modified Silicone (Low Modulus)

1-MS Sealant (Low Modulus) is a one part type modified silicone based sealant which has fast curing property. It is suitable to be applied in areas such as:

1. USE

(EXTERIOR)

*Seam or lap between roofs and wall, sheet metals, construction panels, granite and aluminium frame.

(INTERIOR)

*Joints, gap sealing, general DIY maintenance.

(OTHERS)

*Joint and lap for automotives, marines, and around the frame, tile, and concrete joints.

2. PROPERTIES

Appearance	Paste
Colour	White, Light Grey, Grey, Black.
Viscosity (cps/28±2°C) rotor no.7, 10rpm	350,000-500,000 cps
Specific Gravity (28±2°C)	1.35-1.45
Tack free time (28±2°C)	60 ± 15 minutes
Tensile strength (H-shape)-aluminium (at maximum displacement)	7.5-8.0 kgf/cm ²
Tensile strength (H-shape)-aluminium (at 50% displacement)	2.0-2.5 kgf/cm ²
Elongation (H-shape)	500%
Slump	0 mm

3. CHARACTERISTICS

1-MS Sealant shows the characteristics of:

Adhesion : Excellent adhesion to any substrates especially with primer.

Workability : Stable extrudability in wide temperature range.

Cureability : Fast cure.

Stainability : Non-staining to tiles, mortar and concrete.

In addition, 1-MS Sealant is odourless, no shrinkage, durable and heat uv resistant.

4. PACKING

320ml per cartridge, 20 cartridges per box

600ml per sausage, 20 sausages per box

400ml per sausage, 20 sausages per box

400ml per sausage, 10 sausages per box

5. PRECAUTION

1. Store in cool and dry area.
2. In case of skin contact, clean with thinner and wash thoroughly with soap.

