



# Self-Contained Emergency KELUAR Sign

## PEX-215F (WP) 2 x 8w (Fluorescent Tube) (Weather-Proof Housing)



### Specifications

Model .....	➔	PEX-215F (2 x 8w) -WP (Weather Proof)
Mode .....	➔	Sustained
Weight .....	➔	2.5 Kgs
Battery .....	➔	3 x 1.2V Nickel-Cadmium Battery
Housing .....	➔	Polycarbonate Diffuser And Body (IP 66) Vinyl Stick-on letterings and pictogram
Charger .....	➔	Constant Current
Mounting .....	➔	Surface mounting direct to wall or ceiling
Dimension .....	➔	65 mm (L) x 105 mm (W) x 172 mm (H)
Monitoring .....	➔	Red LED indicating healthy supply and charging
Compliance .....	➔	SIRIM MS 983, IP 65
Light Source .....	➔	Mains on: 1 x 8W Fluorescent Lamp Mains off: 1 x 8W Fluorescent Lamp
Input Voltage .....	➔	240 V +/- 10% 50/60 Hz
Recharge Period .....	➔	16 - 24 Hours
Back Up Duration .....	➔	3 Hours
Power Consumption .....	➔	< 20 VA
Degree of Protection .....	➔	IP - 65
Operating Temperature .....	➔	0°C to 65°C

For further enquiries, please contact :-

**PNE SYSTEMS SDN. BHD.** (263861 D)

No.3, Jalan SS26/13,  
Taman Mayang Jaya 47301, Petaling Jaya,  
Selangor Darul Ehsan, Malaysia

Tel : 603-78037488 (Hunting)

Fax : 603-78038509

E-mail : sales@pnesys.com.my

Website : www.pnesys.com.my