

TECHNICAL SPECIFICATIONS

Model	CP12-20
Ratings	20A @ Current Limit Mode
I/P Voltage	Floating 17V ~ 21V for charging
DC Output	DC 12V (Nominal Output)
DC Charging Output	Auto boost and float charging
Line Regulation (CLM)	0.1 % per V
Load Regulation (CLM)	1%
Visual Indication	LEDs - SOLAR, BATTERY and LOAD
Protection	Solar Input Reversed Polarity Protection Battery Reversed Polarity Protection Output Over-Current and Short-Circuit Electronic Fuse Protection Battery Over-Charging Protection Battery Over-Discharging Cut-Off Protection
I/O Connections	Terminal Blocks for Solar Input, Battery and DC Load
Ambient Temp.	0 ~ 60°C
Relative Humidity	0 ~ 95% non-condensing
Size	W110 x D215 x H55 mm ³
Weight (approx.)	1.2KG

MicroMate®

Low Loss Solar Charger Controller



* Due to the policy of continued product improvement, specifications are subject to change without notice.



Authorised Channel



EMERGING COMPANY
BUSINESS OF THE YEAR
MALAYSIA 2006



CRYSTAL WINNER
BUSINESS SUMMIT
MALAYSIA 2007



INTERNATIONAL GOLD STAR
FOR QUALITY AWARD
(ISQA), GENEVA 2008



KECERMELANGAN PERNIAGAAN BERETIKA
MINISTRY OF DOMESTIC TRADE
CONSUMER AFFAIRS MALAYSIA 2010

