

TECHNICAL SPECIFICATIONS

Model	DCV1224-3
Operation	Switch Mode
Input	DC 12V (Tolerance 10V~16V)
Output Voltage	DC 24V regulated
Output Regulation	±0.3% @100% load
Output Current	3A _{max}
Output Power	72W
Line Regulation	0.01 % per V
Efficiency	≥ 90%
Standby Current	≤ 45mA @ no load
Protection	Input Surge Protection Input Reverse Polarity Protection Output Over-Voltage Clamped Protection Automatic Output Power On Delay
Cooling	Air Cool
Ambient Rating	0 ~ 45°C
Humidity	90% non-condensing
Size (mm ³)	H40 x W70 x D100
Weight (approx)	0.32KG

MicroMate®

12V/24V, 3A DC/DC Converter



* Due to the policy of continued product improvement, specifications are subject to change without notice.



Authorised Channel



EMERGING COMPANY
BUSINESS OF THE YEAR
MALAYSIA 2006



CRYSTAL WINNER
BUSINESS SUMMIT
MALAYSIA 2007



INTERNATIONAL GOLD STAR
FOR QUALITY AWARD
(ISQA), GENEVA 2008



KECERMELANGAN PERNIAGAAN BERETIKA
MINISTRY OF DOMESTIC TRADE
CONSUMER AFFAIRS MALAYSIA 2010