

TE-RTD12

MOTOR RTD MONITORING DEVICE

+ Differential Protection



Advanced Motor Temperature Monitoring Preventive Maintenance

- Can be located at the motor
- Reduced wiring
- Vibration detection via 4-20mA inputs
- Remote monitoring optional
- Digitally communicates with the MVC
- MLink compatible for easy setup



Advanced Motor RTD + Differential Protection

Resistance Temperature Dectector (RTD) + Differential Protection

The TE-RTD12 Relay device adds advanced RTD (Resistor Temperature Detector) and differential current monitoring capability to your new or existing motor system. The TE-RTD12 Relay device offers 12 built-in RTD inputs, 3 programmable output relays (5A), 2 isolated analog inputs (4-20mA), 1 isolated analog output (4-20mA), 3 isolated digital inputs, and differential current monitoring.

Additionally, an RS485 (2 wire) communication port is available for use with a master device (PLC / SCADA / Operator Interface) for the purpose of programming and/or monitoring.

Programmable relay outputs are provided that can be configured for a system function or for use as a global Alarm or Trip based on temperature readout, which can be entered in °C or °F.

A built-in event recorder stores fault history of past events with data points including Alarm Code , Trip Code, Current , Temperature value, Analog input value and Date / Time Stamp.



Specifications

| | |
|----------------------|---|
| Control Voltage: | Universal input range 120 – 240 VAC 50/60Hz |
| Inputs: | 12 RTD inputs (Pt100, Ni100, Ni120, Cu10), 3 CT inputs for differential CT's 2 isolated 4-20mA analog inputs ¹ , 3 isolated Digital Inputs ² |
| Outputs: | 3 programmable form C Relays with 5A contact rating and 1 isolated 4-20mA analog output |
| Keypad: | Two 4-digit displays, one for RTD name, one for Temperature, LEDs for OK, ALARM & TRIP, 3 Output Relay LEDs, Easy to use pushbutton keypad for customer interface. |
| Differential CT's: | Primary 5-2000A, Secondary 1A or 5A, Alarm and Trip Levels OFF, 5% to 90 % of CT value |
| Resolution/Accuracy: | Analog Inputs better than 1%, Analog Outputs better than 0.5% |
| Communication Port: | 2 Wire RS-485 ² , MODBUS RTU |
| I/O Terminals: | Removable terminal blocks |
| Temperature: | Operating 32°F – 122°F / 0°C to 50°C, Storage -4°F to 176°F / -20°C to 80°C |

¹ All analog I/O share a common ground point

² RS485 and Digital Inputs share a common ground point



TE-RTD12 Series

CORPORATE HEADQUARTERS

Motortronics / Phasetronics

1600 Sunshine Drive
Clearwater, Florida 33765
Tel: 727.573.1819 or 888.767.7792
Fax: 727.573.1803 or 800.548.4104
E-mail: sales@motortronics.com
www.motortronics.com

INTERNATIONAL LOCATIONS

Motortronics Int'l Korea Co Ltd

601, Daeryung Techno Tower 5-cha
Gasam-dong, Geumcheon-gu
Seoul, Korea 9153-774
Tel: 82-2-867-5808 / Fax: 82-2-867-6004
www.motortronics-korea.com



M & P Machinery & Electronics Control

113 Zaoshan Road
Qingdao, China 266100
Tel: 86-532-87660633
Fax: 86-532-87660733
www.mp-cn.com

PN: TE-RTD12-060116