

DOUBLE WIDTH TOWER

Build Now - DW1



www.buildnow.com.my

Double Width Build Now Model with Easy Access Stairs



- A - HORIZONTAL BRACE
- B - TOP SIDE
- C - FIX PLATFORM
- D - DIAGONAL BRACE
- E - DOUBLE WIDTH 7 RUNG
WALK THRU FRAME
- F - CASTOR
- G - BALLAST
- H - STABILIZER
- I - EASY ACCESS STAIRS
- J - DOUBLE WIDTH 7 RUNG FRAME
- K - HATCH PLATFORM



SIRIM

PASMA

Certified to BS EN1004:2004

SPECIFICATIONS

DOUBLE WIDTH BUILD NOW MODEL WITH EASY ACCESS STAIRS

Platform Height	2 Meter	3 Meter	4 Meter	5 Meter	6 Meter #a
Tower height	3.70m (8.86ft)	3.27m (10.73ft)	3.66m (11.84ft)	4.13m (13.55ft)	4.70m (15.42ft)
Working height	3.82m (12.54ft)	4.39m (14.41ft)	4.68m (15.36ft)	5.25m (17.23ft)	5.82m (19.10ft)
Primary tower width	4.50m (14.78ft)	5.07m (16.63ft)	5.59m (18.34ft)	6.20m (20.34ft)	6.75m (22.15ft)
Primary tower length				1.48m (4.86ft)	2.00m (6.56ft)
Platform dimension				1.23m x 1.90m (4.04ft x 6.23ft)	
Load Capacity				275 KG	
FASMA United Kingdom & SRM Certification				BS EN 1004 : 2004	

The following are the quantity of 1 set scaffold lower parts:

	2 Meter	3 Meter	4 Meter	5 Meter	6 Meter #a
Double Width 7 Rung Frame	4	2	2	4	4
Double Width 5 Rung Frame	2	0	2	4	2
Double Width 4 Rung Frame	2	2	4	2	4
Double Width Top Side	2	2	2	2	2
Horizontal Brace 2.0 m	4	6	4	6	6
Diagonal Brace 2.0 m	6	4	6	8	10
Hatch Platform 2.0 m	1	1	1	2	1
Roof Platform 2.0 m	1	1	1	1	1
Easy Access Stairs with Landing Platform	1	1	2	2	3
Adjustable Leg c/w 8" Castor Wheel	4	4	4	4	4
Stabiliser Bar 2.50 m	x	x	x	x	x
Stabiliser Bar 4.25 m	x	x	x	x	x
Stabiliser Bar 6.00 m	x	x	x	x	x
Roller 20kg	x	x	x	x	x

Platform Height	6 Meter #b	7 Meter	8 Meter	9 Meter	10 Meter
Tower height	6.10m (20.00ft)	7.22m (23.69ft)	8.12m (26.64ft)	9.26m (30.38ft)	10.11m (33.17ft)
Working height	6.10m (20.00ft)	8.30m (27.23ft)	9.24m (30.32ft)	9.81m (32.19ft)	10.38m (34.06ft)
Primary tower width	6.78m (22.24ft)	7.35m (24.11ft)	7.92m (25.97ft)	8.50m (27.89ft)	9.07m (29.76ft)
Primary tower length				1.48m (4.86ft)	2.00m (6.56ft)
Platform dimension				1.23m x 1.90m (4.04ft x 6.23ft)	
Load Capacity				275 KG	
FASMA United Kingdom & SRM Certification				BS EN 1004 : 2004	

The following are the quantity of 1 set scaffold lower parts:

	6 Meter #b	7 Meter	8 Meter	9 Meter	10 Meter
Double Width 7 Rung Frame	4	4	4	8	8
Double Width 5 Rung Frame	x	x	2	x	2
Double Width 4 Rung Frame	x	2	4	2	4
Double Width Top Side	2	2	2	2	2
Horizontal Brace 2.0 m	4	6	6	6	6
Diagonal Brace 2.0 m	12	12	14	14	18
Hatch Platform 2.0 m	1	1	1	1	1
Roof Platform 2.0 m	1	1	1	1	1
Easy Access Stairs with Landing Platform	4	4	4	5	6
Adjustable Leg c/w 8" Castor Wheel	4	4	4	4	4
Stabiliser Bar 2.50 m	x	x	x	x	x
Stabiliser Bar 4.25 m	x	x	x	x	x
Stabiliser Bar 6.00 m	x	x	x	x	x
Roller 20kg	x	x	x	x	x

Platform Height	11 Meter	12 Meter	13 Meter	14 Meter
Tower height	11.20m (36.75ft)	12.11m (39.73ft)	12.68m (41.60ft)	13.20m (43.47ft)
Working height	12.37m (40.58ft)	13.66m (44.82ft)	13.80m (45.28ft)	14.37m (47.16ft)
Primary tower width	13.25m (43.47ft)	13.34m (43.77ft)	13.91m (45.64ft)	14.48m (47.51ft)
Primary tower length				1.48m (4.86ft)
Platform dimension				2.00m (6.56ft)
Load Capacity				1.23m x 1.90m (4.04ft x 6.23ft)
FASMA United Kingdom & SRM Certification				275 KG
				BS EN 1004 : 2004

The following are the quantity of 1 set scaffold lower parts:

	11 Meter	12 Meter	13 Meter	14 Meter
Double Width 7 Rung Frame	10	10	12	14
Double Width 5 Rung Frame	x	2	x	4
Double Width 4 Rung Frame	2	x	4	2
Double Width Top Side	2	2	2	2
Horizontal Brace 2.0 m	4	4	4	4
Diagonal Brace 2.0 m	20	20	20	24
Hatch Platform 2.0 m	1	2	1	2
Roof Platform 2.0 m	1	1	1	1
Easy Access Stairs with Landing Platform	4	4	7	8
Adjustable Leg c/w 8" Castor Wheel	4	4	4	4
Stabiliser Bar 2.50 m	x	x	x	x
Stabiliser Bar 4.25 m	x	x	x	x
Stabiliser Bar 6.00 m	x	x	x	x
Roller 20kg	x	x	x	x