

SINGLE WIDTH TOWER

Build Now - SW1



[www.buildnow.com.my](http://www.buildnow.com.my)

Single Width Build Now Model with  
Straight Ladder



- A - HORIZONTAL BRACE
- B - TOP SIDE
- C - HATCH PLATFORM
- D - DIAGONAL BRACE
- E - SINGLE WIDTH 4 RUNG LADDER SIDE FRAME
- F - CASTOR
- G - BALLAST
- H - STABILIZER
- I - HATCH PLATFORM
- J - SINGLE WIDTH 4 RUNG FRAME



Certified to BS EN1004:2004

# SPECIFICATIONS

## SINGLE WIDTH BUILD NOW MODEL WITH STRAIGHT LADDER

	< 1 Meter	1 Meter	2 Meter	3 Meter	4 Meter
Platform Height	0.45m (1.31ft)	1.23m (4.00ft)	1.79m (5.67ft)	2.34m (7.48ft)	2.93m (9.41ft)
Tower height	1.83m (6.01ft)	2.40m (7.86ft)	2.97m (9.73ft)	3.56m (11.62ft)	4.11m (13.49ft)
Working height	2.43m (8.04ft)	3.02m (9.91ft)	3.59m (11.78ft)	4.18m (13.62ft)	4.73m (15.52ft)
Primary tower width			0.85m (2.79ft)		
Primary tower length			2.00m (6.56ft)		
Platform dimension			0.60m x 1.90m (1.97ft x 6.23ft)		
Load Capacity			275 KG		
PASMA United Kingdom & SRM Certification			BS EN 1004 : 2004		

The following are the quantity of 1 set scaffold tower parts:

	< 1 Meter	1 Meter	2 Meter	3 Meter	4 Meter
Single Width 4 Rung Normal Side Frame	x	1	x	1	1
Single Width 4 Rung Ladder Side Frame	x	1	x	1	1
Single Width 2 Rung Normal Side Frame	1	x	1	x	1
Single Width 3 Rung Ladder Side Frame	1	x	1	x	1
Single Width 2 Rung Normal Side Frame	x	x	x	x	1
Single Width 2 Rung Ladder Side Frame	x	x	x	x	1
Single Width Top Side	x	x	2	x	2
Horizontal brace 2.0 m	6	6	6	6	6
Diagonal brace 2.0 m	2	2	2	4	6
Hatch Platform 2.0 m	1	1	1	1	1
Adjustable Leg c/w 8" Castor Wheel	4	4	4	4	4
Stabiliser Bar 2.50 m	x	x	x	x	x
Stabiliser Bar 4.25 m	x	x	x	x	x
Stabiliser Bar 6.00 m	x	x	x	x	x
Ballast 20kg	x	x	x	x	x

	5 Meter	6 Meter	7 Meter	8 Meter
Platform Height	1.31m (4.27ft)	1.79m (5.67ft)	2.34m (7.48ft)	2.93m (9.41ft)
Tower height	4.36m (14.29ft)	4.93m (16.16ft)	5.52m (18.09ft)	6.11m (19.99ft)
Working height	7.01m (22.90ft)	7.58m (24.81ft)	8.15m (26.71ft)	8.72m (28.52ft)
Primary tower width			0.85m (2.79ft)	
Primary tower length			2.00m (6.56ft)	
Platform dimension			0.60m x 1.90m (1.97ft x 6.23ft)	
Load Capacity			275 KG	
PASMA United Kingdom & SRM Certification			BS EN 1004 : 2004	

The following are the quantity of 1 set scaffold tower parts:

	5 Meter	6 Meter	7 Meter	8 Meter
Single Width 4 Rung Normal Side Frame	1	2	2	3
Single Width 4 Rung Ladder Side Frame	1	2	3	3
Single Width 3 Rung Normal Side Frame	1	x	1	x
Single Width 3 Rung Ladder Side Frame	1	x	1	x
Single Width 2 Rung Normal Side Frame	1	1	x	1
Single Width 2 Rung Ladder Side Frame	1	1	x	1
Single Width Top Side	2	2	2	2
Horizontal brace 2.0 m	6	6	6	6
Diagonal brace 2.0 m	8	10	12	14
Hatch Platform 2.0 m	1	1	1	1
Adjustable Leg c/w 8" Castor Wheel	4	4	4	4
Stabiliser Bar 2.50 m	x	x	x	x
Stabiliser Bar 4.25 m	x	x	x	x
Stabiliser Bar 6.00 m	x	x	x	x
Ballast 20kg	x	x	x	x

	9 Meter	10 Meter
Platform Height	1.31m (4.27ft)	1.79m (5.67ft)
Tower height	10.36m (34.09ft)	11.52m (37.80ft)
Working height	11.00m (36.09ft)	12.14m (39.83ft)
Primary tower width		0.85m (2.79ft)
Primary tower length		2.00m (6.56ft)
Platform dimension		0.60m x 1.90m (1.97ft x 6.23ft)
Load Capacity		275 KG
PASMA United Kingdom & SRM Certification		BS EN 1004 : 2004

The following are the quantity of 1 set scaffold tower parts:

	9 Meter	10 Meter
Single Width 4 Rung Normal Side Frame	4	4
Single Width 4 Rung Ladder Side Frame	4	4
Single Width 3 Rung Normal Side Frame	x	x
Single Width 3 Rung Ladder Side Frame	x	x
Single Width 2 Rung Normal Side Frame	x	1
Single Width 2 Rung Ladder Side Frame	x	1
Single Width Top Side	2	2
Horizontal brace 2.0 m	6	6
Diagonal brace 2.0 m	14	18
Hatch Platform 2.0 m	1	1
Adjustable Leg c/w 8" Castor Wheel	4	4
Stabiliser Bar 2.50 m	x	x
Stabiliser Bar 4.25 m	x	x
Stabiliser Bar 6.00 m	4	4
Ballast 20kg	4	4