


BT / NT
series

BCA

Micro Boring Holder

微調精搪刀桿



- Boring head must be ordered separately.
- 精搪頭為另購品




Model No.	Boring Range		D	D1	L	Boring Head	Weight (kg)
	Min.	Max.					
BT30 BCA025-150	25	29	22	25	150	L148C-31	0.80
BCA026-150	26	30	23	26	150	L148C-31	0.90
-180	26	30	23	26	180	L148C-31	1.00
BCA030-160	30	34	26	30	160	L148C-31	1.10
-210	30	34	26	30	210	L148C-31	1.40
BCA033-165	33	38	29	33	165	L148C-32	1.30
-210	33	38	29	33	210	L148C-32	1.70
BCA038-165	38	43	33	38	165	L148C-32	1.40
-210	38	43	33	38	210	L148C-32	1.70
BCA043-165	43	52	38	43	165	L148C-33	1.80
-210	43	52	38	43	210	L148C-33	2.00
BCA052-180	52	61	47	52	180	L148C-33	2.30
-240	52	61	47	52	240	L148C-33	2.80
BCA061-180	61	70	56	61	180	L148C-33	2.40
-240	61	70	56	61	240	L148C-33	2.60
-330	61	70	56	61	330	L148C-33	3.00
BCA070-180	70	85	65	70	180	L148C-34	2.80
-240	70	85	65	70	240	L148C-34	3.00
-330	70	85	65	70	330	L148C-34	3.50
BT40 BCA025-150	25	29	22	25	150	L148C-31	1.50
BCA026-150	26	30	23	26	150	L148C-31	1.50
-180	26	30	23	26	180	L148C-31	1.70
BCA030-160	30	34	26	30	160	L148C-31	1.80
-210	30	34	26	30	210	L148C-31	1.90
BCA033-165	33	38	29	33	165	L148C-32	1.80
-210	33	38	29	33	210	L148C-32	1.90
BCA038-165	38	43	33	38	165	L148C-32	2.10
-210	38	43	33	38	210	L148C-32	2.50
BCA043-165	43	52	38	43	165	L148C-33	2.30
-210	43	52	38	43	210	L148C-33	2.80
BCA052-180	52	61	47	52	180	L148C-33	3.30
-240	52	61	47	52	240	L148C-33	4.30
BCA061-180	61	70	56	61	180	L148C-33	4.10
-240	61	70	56	61	240	L148C-33	5.20
BCA070-180	70	85	65	70	180	L148C-34	4.30
-240	70	85	65	70	240	L148C-34	5.80
BCA085-180	85	100	80	85	180	L148C-34	5.20
-240	85	100	80	85	240	L148C-34	6.90
BCA100-165	100	115	95	100	165	L148C-34	6.10
-240	100	115	95	100	240	L148C-34	7.50

Unit: mm

Micro Boring Holder

微調精搪刀桿



BCA

BT / NT

series



- Boring head must be ordered separately.
- 精搪頭為另購品



Model No.	Boring Range		D	D1	L	Boring Head	Weight (kg)
	Min.	Max.					
BT50 BCA025-150	25	29	22	25	150	L148C-31	4.30
BCA026-150	26	30	23	26	150	L148C-31	4.30
-180	26	30	23	26	180	L148C-31	4.40
BCA030-160	30	34	26	30	160	L148C-31	4.40
-210	30	34	26	30	210	L148C-31	4.60
BCA033-165	33	38	29	33	165	L148C-32	4.50
-210	33	38	29	33	210	L148C-32	4.80
BCA038-165	38	43	33	38	165	L148C-32	4.70
-210	38	43	33	38	210	L148C-32	5.20
BCA043-165	43	52	38	43	165	L148C-33	5.00
-210	43	52	38	43	210	L148C-33	5.30
BCA052-180	52	61	47	52	180	L148C-33	5.60
-240	52	61	47	52	240	L148C-33	6.70
BCA061-180	61	70	56	61	180	L148C-33	6.60
-240	61	70	56	61	240	L148C-33	7.40
-330	61	70	56	61	330	L148C-33	9.40
BCA070-180	70	85	65	70	180	L148C-34	7.30
-240	70	85	65	70	240	L148C-34	9.00
-330	70	85	65	70	330	L148C-34	10.90
BCA085-180	85	100	80	85	180	L148C-34	8.30
-240	85	100	80	85	240	L148C-34	10.10
-330	85	100	80	85	330	L148C-34	12.00
BCA100-165	100	115	95	100	165	L148C-34	8.40
-240	100	115	95	100	240	L148C-34	10.60
-315	100	115	95	100	315	L148C-34	12.50
BCA115-165	115	130	110	115	165	L148C-34	8.60
-240	115	130	110	115	240	L148C-34	10.80
-315	115	130	110	115	315	L148C-34	12.70
BCA130-165	130	145	125	130	165	L148C-34	9.00
-240	130	145	125	130	240	L148C-34	10.50
BCA145-165	145	160	140	145	165	L148C-34	9.50
-240	145	160	140	145	240	L148C-34	11.00

Unit: mm

Square Micro Boring Holder

方型精搪刀桿



MBT



- Boring head must be ordered separately.
- 精搪頭為另購品

Model No.	Applicable Angle	L	L1	W□	Boring Head
MBT16-L	30°, 45°, 90°	80, 130	30	16	L148C-31
MBT19/19.05-L	30°, 45°, 90°	100, 150, 200	30	19/19.05	L148C-31
MBT25/25.4-L	30°, 45°, 90°	100, 150, 200	30	25/25.4	L148C-31

Unit: mm