

Portable Air Tapper



NEW

JIS STANDARD TAP



VAT-308P



VAT-612P

- Light weight.
- Suitable for big workpiece.
- Powerful.
- Easy operation.
- Required air pressure 6kg/cm²

- Air consumption is 0.25 l/min.
- Required install air combination.
- Lubricate air inlet connector with 3 c.c. oil. Always before and after using.



SET TYPE

ORDER NO.	TAPPING CAPACITY	COLLET SET (pcs/set)	WORKING SPEED (Y.P.M.)	SPINDLE SPEED (R.P.M.)	HOSE CONNECT SIZE	OVERALL LENGTH (mm)	N.W. (kgs)	CUFT	CODE NO.
VAT-308P	M3~M8	5 pcs	350	8500	PT 1/4"	158 mm	0.9	0.13	3404-471
VAT-612P	M6~M12	4 pcs	280	8000	PT 1/4"	168 mm	1.1	0.13	3404-472

ACCESSORIES COLLET SIZE pcs / set

ORDER NO.	ØD x JIS STD. FOR TAP SIZE	pcs/ set	N.W. (kgs)	CODE NO.
VAT-308PC	M3 (Ø 4 x 3.2) x 1pcs M4 (Ø 5 x 4) x 1pcs M5 (Ø 5.5 x 4.5) x 1pcs M6 (Ø 6 x 4.5) x 1pcs M8 (Ø 6.2 x 5) x 1pcs	5 pcs/set	0.2	3404-481
VAT-612PC	M6 (Ø 6 x 4.5) x 1pcs M8 (Ø 6.2 x 5) x 1pcs M10 (Ø 7 x 5.5) x 1pcs M12 (Ø 8.5 x 6.5) x 1pcs	4 pcs/set	0.3	3404-482