Fridge or Freezer Thermometer supplied with a UKAS Certificate of Calibration



- monitors both internal & external temperatures
- calibrated to UKAS standards

This fridge or freezer thermometer features a max/min function, audible alarm and is supplied with a two-point UKAS Certificate of Calibration. Each certificate indicates deviations from standards at various check points: -18 and 0 °C.

The thermometer features a large LCD display and incorporates two temperature sensors; a remote water resistant probe with one metre PVC lead for the appliance temperature and an internal sensor for the room temperature. The remote probe can be mounted onto the internal wall of the fridge using the suction pad or mounting bracket supplied.

The thermometer is housed in a durable ABS case and incorporates a foot-stand for shelf mounting.

order code	description	
891-210	digital fridge/freezer thermometer	
UKAS calibration applies to remote probe only		

DishTemp® dishwasher thermometer

- displays maximum temperature reached
- simulates plate surface temperature

The new DishTemp thermometer simulates a plate as it's cleaned and sanitised in a commercial dishwasher, accurately recording the maximum surface temperature at the touch of a single button. The DishTemp eliminates the need for costly and inaccurate test strips and stem thermometers that don't stay in place and don't record temperature at the plate surface.

Built to survive daily use in professional kitchens, the DishTemp thermometer indicates temperature over the range of 0 to 90 °C with a resolution of 0.1 °C/°F and an accuracy of ± 0.5 °C.

Incorporating a durable water-tight seal, the DishTemp is waterproof to IP66 and is supplied complete with a traceable certificate of calibration.

order code	description	
810-280	DishTemp thermometer	

NEW	CERTIFICATE OF CALIBRATION MXXVIII Visiting	
FRIDGE / FREE	Pindue Alexandro Parmie 44 2002 2004	nature Commente
THERMOMETE		UKAS
specification	digital fridge/freezer	
range	-49.9 to 69.9 °C	
resolution	0.1 °C/°F	
accuracy	±1 °C	
battery & life	1.5 volt AAA - 5000 hours	
display	custom LCD	
dimensions	15 x 52 x 73 mm	
weight	55 grams	
a UKAS Ce	ertificate of Calibration is included	

也 IP66 °C/°F 0 to 90 °C range resolution 0.1 °C/°F accuracy ±0.5 °C 3 volt CR2032 lithium coin cell battery battery life 5000 hours display custom LCD dimensions 14 x Ø127 mm 120 grams weight FREE traceable certificate of calibration included

