

Product Specifications

FlashCheck. Waterproof Min/Max Folding Probe Thermometer

Measurement Range	-58°F to 572°F (-50°C to 300°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1.8°F (-4°F to 392°F); ±1°C (-20°C to 200°C)
Response Time	Under 4 seconds
Sensor	Thermistor
Display Resolution	0.2°F / 0.1°C
Display Reading Update	Every 0.25 seconds
Display Window Size	1.68 in W x 0.65 in H (42.7mm W x 16.6mm H)
Calibration	Automatic Calibration button
Battery	CR2032 3V Li coin cell battery
Auto Shut-Off	10 minutes
Body Casing	ABS Plastic
Probe Length	4.7in (120mm)
Probe Diameter	Food grade safety 304 stainless steel probe 0.067in (1.7mm)
Waterproof Rating	IP67
Factory Calibration	NIST traceable calibration



Model 15051

- Instant temperature reading
- Foldable probe for safe handling
- Magnetic back surface
- Hold feature locks temperature reading
- Ideal for thin mass foods such as meat patties, chicken and fish fillets
- Min/Max memory stores lowest/highest readings
- °F/°C selectable
- Measures up to 572°F (300°C)
- Backlit display
- Automatic calibration feature
- Highly visible dual scale jumbo LCD display
- IP67 waterproof, sanitizable, dirt and grease resistant
- Powers on automatically when unfolding probe
- Automatic shut off saves battery life
- Complies with FDA Food Code 4-203.11

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 15051 20C1

