

SP 24-46 SG (604113000) Construction and Dirty Water Pump Cardboard box

Order no. 604113000
EAN 4007430221551



Product may differ from Image



- For drainage and pumping dry of construction pits, cellars and shafts. Also for pumping sewage and waste water in industrial and domestic environments.
- Mechanical seal for protection of the pump if the water is particularly dense or contains large particles
- Self-cleaning Vortex-impeller to minimise blockages
- Designed for continuous mode with S1 motor operating mode
- Overload protection: protects the motor from overheating
- Float switch for automatic mode
- Suitable for mobile and stationary use thanks to ergonomic handles and stability

Technical data**Characteristics**

Rated input power	900 W
Maximum delivery rate	24000 l/h / 6340 gal/h
Maximum delivery height	9 m / 30 ft
Maximum pressure	0.9 bar / 13.1 psi
Maximum immersion depth	7 m / 23 ft
Discharge port	2" female thread
Pump housing	Grey cast iron
Maximum particle size up to	46 mm / 1 13/16 "
Number of impellers	1
Dimensions	275 x 210 x 412 mm / 10 13/16 x 8 1/4 x 16 7/32 "
Weight	17.9 kg / 39.5 lbs
Cable length	10 m / 33 ft

Scope of delivery

Float switch