Cavo Technology

FIBER OPTIC WALL MOUNTED TERMINAL BOX (SINGLE DOOR)

FEATURES:

- Indoor Wall-mount distribution frame can manage for both single fiber and ribbon & bundle fiber special design ensures the excess fiber cords & pigtails in good order
- They have various panel to fit different adapter interface like FC, SC, ST, LC Suitable for LAN / WAN, CATV application

APPLICATION:

- •Local Area Network (LAN)
- •Optical Access Network (OAN)
- •Data Processing Centers
- Cable Television (CATV)
- •FTTH





24 Port

SPECIFICATION

ITEM		CHARACTERISTICS	
Operation Temperature		-25°C~+40°C	
Storage Temperature		-25°C~+55°C	
Relative Humidity		≤85%(+30°C)	
Air Pressure		70Kpa~106Kpa	
Colour		Beige and Black	
PORT	DIMENSION(DxWxH)		CAPACITY
12 Port	65mm×300mm×265mm		12 fiber
24 Port	94mm×262mm×300mm		24 fiber

Ordering Information

Connector Type: SC, LC, FC, ST
Ferrule End-face: PC, UPC, APC

3. Part Number: CV-WMWWUU-YY WW=Connector Type YY= SM/MM UU= 12 / 24 / 48 (Total Ports)