



### Main

Range	Actassi
Product or component type	Copper cable
Colour tint	Blue
Cable shielding type	U/UTP

### Complementary

Type of cable	4 pair cables
Communication network category	6
Minimum return loss	Guaranteed: 19.4 dB at 0.772 MHz Guaranteed: 20 dB at 1 MHz Guaranteed: 23 dB at 4 MHz Guaranteed: 24.5 dB at 8 MHz Guaranteed: 25 dB at 10 MHz Guaranteed: 25 dB at 16 MHz Guaranteed: 25 dB at 20 MHz Guaranteed: 24.3 dB at 25 MHz Guaranteed: 23.6 dB at 31.25 MHz Guaranteed: 21.5 dB at 62.5 MHz Guaranteed: 20.1 dB at 100 MHz
Attenuation	Guaranteed: 1.8 dB @ 0.772 MHz per 100 m cable Guaranteed: 2 dB @ 1 MHz per 100 m cable Guaranteed: 4.1 dB @ 4 MHz per 100 m cable Guaranteed: 5.8 dB @ 8 MHz per 100 m cable Guaranteed: 6.5 dB @ 10 MHz per 100 m cable Guaranteed: 8.2 dB @ 16 MHz per 100 m cable Guaranteed: 9.3 dB @ 20 MHz per 100 m cable Guaranteed: 10.4 dB @ 25 MHz per 100 m cable Guaranteed: 11.7 dB @ 31.25 MHz per 100 m cable Guaranteed: 17 dB @ 62.5 MHz per 100 m cable Guaranteed: 22 dB @ 100 MHz per 100 m cable
Power sum near-end crosstalk [PSNEXT]	Guaranteed: 64 dB at 0.772 MHz Guaranteed: 62.3 dB at 1 MHz Guaranteed: 53.3 dB at 4 MHz Guaranteed: 48.8 dB at 8 MHz Guaranteed: 47.3 dB at 10 MHz Guaranteed: 44.3 dB at 16 MHz Guaranteed: 42.8 dB at 20 MHz Guaranteed: 41.3 dB at 25 MHz Guaranteed: 39.9 dB at 31.25 MHz Guaranteed: 35.4 dB at 62.5 MHz Guaranteed: 32.3 dB at 100 MHz

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Near end crosstalk [NEXT]	Guaranteed: 67 dB at 0.772 MHz Guaranteed: 65.3 dB at 1 MHz Guaranteed: 56.3 dB at 4 MHz Guaranteed: 51.8 dB at 8 MHz Guaranteed: 50.3 dB at 10 MHz Guaranteed: 47.3 dB at 16 MHz Guaranteed: 45.8 dB at 20 MHz Guaranteed: 44.3 dB at 25 MHz Guaranteed: 42.9 dB at 31.25 MHz Guaranteed: 38.4 dB at 62.5 MHz Guaranteed: 35.3 dB at 100 MHz
Input impedance	100 Ohm (+/- 6) at 1...100 MHz
Maximum loop resistance	73.2 Ohm
Capacitance unbalance	330 PF / 100 m
Maximum resistance unbalance	5 %
Wire insulation material	PE
Conductor material	Solid bare copper
AWG gauge	AWG 23
Cable outer diameter	4.9 Mm
Cable length	305 M

## Environment

Ambient air temperature for operation	75 °C
Product certifications	UL
Flame retardance	CM
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801 UL 444

## Packing Units

Package 1 Weight	12300.000 G
Package 1 Height	350.000 Mm
Package 1 width	270.000 Mm
Package 1 Length	330.000 Mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**