

# Cavo Technology

## ODF SPLICE MODULE

### FEATURES:

- Standard size, light weight and reasonable structure
- Splice tray inside changeable
- Can be used in 19", 23" standard distribution frame
- Suitable for ribbon and single fiber
- Various panel plate to fit different adapter interface
- Front mark on the plate is easy for identification and operation
- 12C, 24C, 48C, 72C, 96C, 144C optional, with or without fiber optic pigtails and adapters
- Easy for management and operation



### APPLICATION:

- Telecommunications subscriber loop
- Fiber to the home (FTTH)
- LAN/WAN
- CATV

### SPECIFICATION

CORE COUNT	HEIGHT	DIMENSION (mm)	WEIGHT (kg)
12	1U	45 X 430 X 270	4.6
24	2U	70 X 430 X 270	5.4
48	3U	140 X 430 X 270	7
72	4U	200 X 430 X 270	9
96	5U	255 X 430 X 270	11
144	7U	334 X 430 X 270	17.1

### Ordering Information

1. Connector Type: SC, LC, FC (PC/UPC/APC)
2. Part Number: CV-ODFR-UUWW R=1U/2U/3U/4U 5U/7U(Height) WW=Connector Type  
UU=12/ 24/ 48/ 72/ 96/ 144 (Total Ports)