

Detailed Specifications & Technical Data



AX104448 86×86 Key Connect – Tilted Double Port - Faceplate



For more information please
call
1-800-Belden1



[See Put-ups and Colors](#)

Description:

86×86 key connect, tilted double port, UK style faceplate (white)

SUITABLE APPLICATIONS:

Suitable Applications

Faceplate in work area environments

Support current and future Category 5e, 6 and 6a Keystone connectivity

OUTLET SPECIFICATION:

FACEPLATE:

Material	Flame Retardant Plastic UL-94V0, ABS (Acrylonitrile Butadiene Styrene)
Dimensions	(H x W x D) 86 x 86 x 25.6 mm
Mounting screws	2 pcs, M3.5 x 25mm

APPLICABLE STANDARDS & ENVIRONMENTAL PROGRAMS:

RoHS Compliant	Yes
----------------	-----

SUITABILITY:

Suitability - Indoor	Yes
----------------------	-----

FLAME TEST:

UL Flame Test For Material	UL-94 V0
----------------------------	----------

PUT-UPS AND COLOR:

Item	Description	Put-Up* (pcs)	Ship Weight(kg)	Color
AX104448	86×86 KEY CONNECTOR TILTED DOUBLE PORT FACEPLATE	400	15	WHITE

* Individually packaged in a clear plastic bag.

Detailed Specifications & Technical Data



AX104448 86×86 Key Connect – Tilted Double Port - Faceplate

Revision Number: 1

Revision Date: 5/14/2013

©Copyright 2013 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.