



### Main

Range	Actassi
Product or component type	Patch cord
Colour	Blue
Cable shielding type	UTP

### Complementary

Type of cable	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Length	0...2 M
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 MOhm
AWG gauge	AWG 24
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 DB
Power sum far end crosstalk [PSFEXT]	46.9 DB
Minimum number of matings	1000 Cycles
Targeted region	Asia Pacific.

### Environment

Flame retardance	CM
Standards	IEC 60603-7 FCC part 68 subpart F AS/NZS 3080:2003 TIA/EIA-568-B ISO/IEC 11801 2nd edition

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	105 G
Package 1 Height	1 Cm
Package 1 width	21 Cm
Package 1 Length	30.2 Cm
Unit Type of Package 2	CAR

Number of Units in Package 2	90
Package 2 Weight	10.5 Kg
Package 2 Height	42 Cm
Package 2 width	62 Cm
Package 2 Length	27 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**