



Main

Range	Actassi
Product or component type	Patch cord
Colour	Blue
Cable shielding type	UTP

Complementary

Type of cable	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Length	0...1 M
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 MOhm
AWG gauge	AWG 24
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 DB
Power sum far end crosstalk [PSFEXT]	46.9 DB
Minimum number of matings	1000 Cycles
Targeted region	Asia Pacific.

Environment

Flame retardance	CM
Standards	IEC 60603-7 FCC part 68 subpart F AS/NZS 3080:2003 TIA/EIA-568-B ISO/IEC 11801 2nd edition

Packing Units

Package 1 Weight	50.000 G
Package 1 Height	302.000 Mm
Package 1 width	0.080 Mm
Package 1 Length	210.000 Mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. announced**

ACTPC6UBCM10BU may be replaced by any of the following products:



ACTPC6UUCM10BU

Patch cord, Actassi, Category 6, U/UTP, PVC, 1 m, blue

Qty 1

Substitution date: |