CA111H2



GigaSPEED X10D® G10SP on S/FTP Cordage, S/FTP Modular Patch Cord

Product Classification

Regional Availability

Asia | Australia/New Zealand | Latin America | North America

Portfolio SYSTIMAX®

Product Type Twisted pair patch cord

Product Brand GigaSPEED X10D®

Product Series CA

Ordering Note Cords < 1 m are valid elements for use in a channel or as an equipment interconnect but

due to their limited length are not guaranteed to meet component compliance requirements that were developed to assess the quality of longer cords | Cords > 1 m are authorized for use in channels and are an effective standalone method used to connect active devices

General Specifications

ANSI/TIA Category 6A

Cable Type S/FTP (shielded)

Conductor Type Stranded
Interface, Connector A RJ45 plug
Interface Feature, connector A Standard
Interface, Connector B RJ45 plug
Interface Feature, connector B Standard

Jacket Color Black | Blue | Green | Orange | Purple | Red | Slate | Violet | White | Yellow

Pairs, quantity 4

Transmission Standards IEEE 802.3bt Type 4

Wiring T568B

Dimensions

Cable Assembly Length Range (m) 1 - 30

Cable Assembly Length Range (ft) 1 - 100



CA111H2

Cable Assembly Length Range (cm)15 - 999Cable Assembly Length Range (in)6 - 999

Diameter Over Jacket 5.7 mm | 0.224 in

Wiring Diagram

	Connector A	Connector B
Position 1	White/Orange	White/Orange
Position 2	Orange	Orange
Position 3	Lt. Green	Lt. Green
Position 4	Blue	Blue
Position 5	Lt. Blue	Lt. Blue
Position 6	Green	Green
Position 7	Lt. Brown	Lt. Brown
Position 8	Brown	Brown

Electrical Specifications

dc Resistance, maximum0.3 ohmSafety Voltage Rating300 V

Material Specifications

Contact Plating Material Precious metals

Material Type Copper alloy | Polycarbonate

Mechanical Specifications

Plug Insertion Life, minimum 750 times

Plug Retention Force, minimum 133 N | 29.9 lbf

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$

Environmental SpaceNon-plenumFlammability RatingUL 94 V-0Safety StandardETL | cETL

COMMSCOPE®

CAlllH2

Packaging and Weights

Packaging quantity

1

