Essential-6 Patch Cords

Essential-6 Patch Cord UTP Cat 6 PVC Grey 2m

Contact sales

datanetworks.sg@nexans.com

Nexans Ref.: N101.11EEGG

- · Compliant with latest Category 6 standards
- Unscreened
- · Light grey PVC
- · Light grey slimline boot with bend relief
- 2m length

DESCRIPTION

Application

The Nexans Essential-6 patch cords are manufactured and tested to the latest Category 6 specifications and support Class E applications up to 250 MHz. They are matched with the complete Essential-6 range in order to deliver a full end-to-end Class E Channel.

Design

The Essential-6 patch cords contain a central PE cross member, keeping the pairs in place and reducing the risk of losing performance when bending the cords. Available in standard lengths of 1, 2, 3 and 5m, each cord is individually bagged and carries a traceability code.

Performance

The Essential-6 cords are compliant with the specifications of ISO/IEC 11801 and EN 50173.

Installation

Thanks to their small outer diameter, the Essential-6 cords are easy to install and manage in a rack.



essential-6

STANDARDS

International ISO/IEC 11801



IEC 60332-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is ndicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.







Essential-6 Patch Cords

Essential-6 Patch Cord UTP Cat 6 PVC Grey 2m

Contact sales datanetworks.sg@nexans.com

CHARACTERISTICS

Construction characteristics	
Screen	UTP
Colour	Light grey
Outer sheath	PVC
Dimensional characteristics	
Conductor cross-section (AWG/KCMIL)	-
Electrical characteristics	
Characteristic impedance	100 Ohm
Usage characteristics	
Category	Cat. 6
Component function	Patchcord
Flame retardant	IEC 60332-1
Length	2 m
Mechanical durability/matings	-
Range	essential-6

