760237040 | CPP-UDDM-SL-1U-24

Discrete Distribution Module Panel, SL, UTP, 1U, 24 port



Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North

America

PortfolioCommScope®Product TypeRJ45 patch panel

General Specifications

ANSI/TIA Category 5e | 6 | 6A

Cable Type Unshielded

Color Black

Modules, quantity 0

Panel StyleStraightRack TypeEIA 19 in

Rack Units 1

Total Ports, quantity 24

Dimensions

Height44.45 mm| 1.75 inWidth482.6 mm| 19 inDepth, with cable management119.38 mm| 4.7 inCompatible Diameter Over Dielectric, maximum1.168 mm| 0.046 in

Compatible Diameter Over Dielectric, minimum 0.762 mm | 0.03 in

Material Specifications

Material Type High-impact, flame retardant, thermoplastic | Powder-coated steel



760237040 | CPP-UDDM-SL-1U-24

Environmental Specifications

Operating Temperature -10 °C to +60 °C (+14 °F to +140 °F)

Storage Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Flammability Rating UL 94 V-0

Safety Standard RCM | UL | cUL

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Classification **Agency**

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



